



Contribution ID: 370

Type: Poster

## EX/P2-02: ITER Demonstration Discharges on Alcator C-Mod in Support of ITER

*Tuesday, 9 October 2012 14:00 (4h 45m)*

Alcator C-Mod is providing discharges that match several simultaneous parameters expected in ITER in the rampup, flattop and rampdown phases, and simulations of these discharges with time-dependent transport evolution codes. Discharges have been produced at both  $B = 5.4$  T and 2.7 T, utilizing H-minority heating fundamental and 2nd harmonic, respectively. Discharges with rampup durations appropriate to ITER's show that ICRF heating obtains V-s savings with only weak effects on the current profile, in spite of strong modifications of the central electron temperature. Significant V-s savings in ohmic rampup by utilizing lower densities appears only to be effective at very low density,  $n/n_{Gr} \sim 0.08$ . Injection of lower hybrid during the rampup is effective for saving V-s, again only at similarly low densities. Simulations of C-Mod rampup discharges have been performed with the Tokamak Simulation Code (TSC), utilizing TORIC full wave calculation of the ICRF deposition, and using the Current Diffusive Ballooning (CDBM), Bohm-gyro Bohm, Coppi-Tang, and modified GLF23 (enhanced thermal diffusivity near plasma edge) transport models showing that they are not reproducing the temperature profile evolution, and consequently do not reproduce the experimental internal self-inductance or the V-s. Discharges which obtained EDA H-modes during flattop, with  $B = 2.7$  T and  $I_p = 0.65$  MA, obtain parameter values between  $(bN, n/n_{Gr}, H98) = (1.9, 0.60, 1.0)$  to  $(1.5, 0.8, 0.67)$ . The lower  $n/n_{Gr}$  values are associated with the higher H98 and bN. Discharges showed a degradation of the energy confinement as the higher densities were approached, but also an increasing H98 with net power to the plasma ( $P_{net} = PICRF + POH - dW/dt - Prad$ ). For these discharges up to 3 MW was injected, while intrinsic impurities (B, Mo) provided radiated power fractions ( $Prad/P_{in}$ ) of 25-37%, typical of those required in ITER. Experiments at 5.4 T have demonstrated the plasma can remain in H-mode as the rampdown phase is entered with at least 0.75 MW of ICRF injection, the back transition occurring when the net power reaches 1 MW, and the density will decrease at the same rate as  $I_p$  when in H-mode, maintaining the flattop  $n/n_{Gr}$  value. Maintaining the H-mode longer into the rampdown and ramping the plasma current down faster can mitigate the OH coil over-current associated with the back transition.

### Country or International Organization of Primary Author

USA

**Primary author:** Mr KESSEL, Charles E. (USA)

**Co-authors:** Dr MIKKELSEN, D. R. (PPPL); Dr POLI, F. (PPPL); Dr HUTCHINSON, I. H. (MIT/PSFC); Dr HUGHES, J. W. (MIT/PSFC); Dr REINKE, M. L. (MIT/PSFC); Dr WUKITCH, S. J. (MIT/PSFC); Dr WOLFE, S. M. (MIT/PSFC); Dr LIN, Y. (MIT/PSFC); Dr MA, Y. (MIT/PSFC)

**Presenter:** Mr KESSEL, Charles E. (USA)

**Session Classification:** Poster: P2

**Track Classification:** EXC - Magnetic Confinement Experiments: Confinement