

Contribution ID: 16

Type: Poster

## IFE/P6-16: Summary of Progress in U.S. Heavy Ion Fusion Science Research

Thursday, 11 October 2012 14:00 (4h 45m)

Construction of the Neutralized Drift Compression eXperiment (NDCX-II), a new high-current, moderatekinetic-energy accelerator facility at LBNL, is being completed in the spring of 2012. The machine will produce a nanosecond Li+ ion beam bunch at ~2 MeV energy for volumetric heating of thin foils. Extensive simulations using the Warp code led to a physics design with specialized acceleration voltage waveforms that can achieve >500-fold longitudinal beam compression. Planned experiments on NDCX-II to study warm dense matter include: measuring equation of state and phase transitions, conductivity, opacity and shock generation. Theoretically, we have: (a) studied transverse and longitudinal beam compression on two-stream interactions of an intense ion beam in plasma; (b) studied transverse gradients and profile shapes on beamplasma instabilities; (c) identified a class of self-consistent periodic kinetic 'equilibria' for intense beams in alternating-gradient focusing systems, and extended nonlinear perturbative particle simulations to such focusing systems; (d) investigated nonlinear effects of beam-plasma instabilities on beam current neutralization; (e) proposed a Rayleigh-Taylor instability mechanism for droplet formation in expanding warm dense matter; and (f) carried out theoretical studies of using a beam "wobbler"(periodic deflector) as a beam smoothing technique.

Using HYDRA simulations to design the novel Heavy Ion Fusion X-target, it was found that, by adding an aluminum pusher and radial tamping, the fusion gain can be increased from 50 to 300, and the stagnation fuel density doubled to 100 g/cm<sup>3</sup> at peak compression, with a "rho-r" <sup>2</sup> g/cm<sup>2</sup>. The X-target has a simple cylindrical metal case filled with DT fuel and a conical insert with an "X"shaped cross-section. Using multiple heavy ion beams to illuminate the target axially from only one side, the fuel can be compressed and ignited at the X-vertex. The simulations showed negligible RT growth leaving a central clean DT ignition zone. We have also developed a directly driven, spherical, tamped, hot-spot ignited target that has high hydrodynamic efficiency while relaxing accelerator phase-space constraints. This target is driven by a combination of an exploding pusher followed by radiation driven ablation.

## **Country or International Organization of Primary Author**

USA

## Primary author: Mr KWAN, Joe (USA)

**Co-authors:** Dr FRIEDMAN, Alex (LLNL); Dr GROTE, David (LLNL); Dr STARTSEV, Ed (PPPL); Dr HEN-ESTROZA, Enrique (LBNL); Dr GILSON, Erik (PPPL); Dr LOGAN, Grant (LBNL); Dr QIN, Hong (PPPL); Dr KAGANOVISH, Igor (PPPL); Dr BARNARD, John (LLNL); Dr PERKINS, John (LLNL); Dr GRISHAM, Larry (PPPL); Dr TERRY, Matt (LLNL); Dr NI, Pavel (LBNL); Dr SEIDL, Peter (LBNL); Dr EFTHIMION, Philip (PPPL); Dr ROY, Prabir (LBNL); Dr MORE, Richard (LLNL); Dr COHEN, Ron (LLNL); Dr DAVIDSON, Ron (PPPL); Dr LIDIA, Steve (LBNL); Dr LUND, Steve (LLNL); Dr SHARP, William (LLNL); Mr WALDRON, William (LBNL)

Presenter: Mr KWAN, Joe (USA)

## Session Classification: Poster: P6

Track Classification: IFE - Inertial Fusion Experiments and Theory