



Contribution ID: 427

Type: Poster

FTP/P1-11: Plasma Characteristics of the End-cell of the GAMMA 10 Tandem Mirror for the Divertor Simulation Experiment

Tuesday, 9 October 2012 08:30 (4 hours)

In this paper, detailed characteristics and controllability of plasmas emitted from the end-cell of the GAMMA 10 tandem mirror are described from the viewpoint of divertor simulation studies. In the case of only ICRF plasma, the heat flux of 0.8 MW/m^2 has already been achieved and proportionally increased with the ICRF power for ion heating. The energy analysis of ion flux by using end-loss ion energy analyzer (ELIEA) proved that the obtained high ion temperature (100 - 400 eV) was comparable to SOL plasma parameters in toroidal devices and was controlled by changing the ICRF power. Parallel ion temperature $T_{i\parallel}$ determined from the probe and calorimeter shows a linear relationship with the stored energy in the central-cell and agrees with the results of ELIEA. Recently additional plasma heating experiment using ICRF in the anchor-cell (RF3) was carried out in order to improve the performance. The time behavior of the plasma line-density and end-loss ion flux is shown in Fig. 4. A significant enhancement of the line-density is observed and the resultant ion flux becomes two times higher than that without RF3. The particle flux is estimated to be $6.5 \times 10^{22} \text{ particles/s} \cdot \text{m}^2$, which indicate an effectiveness of additional heating with ICRF wave in the neighboring cells toward the improved E-divertor experiments for achieving the targeted parameters of this project (PHEAT $\sim 20 \text{ MW/m}^2$, $T_i = 10^{23-24} / \text{m}^2 \text{ sec}$).

We have started various experiments such as radiator gas injection onto the tungsten target and visible measurement of plasma-gas-material interactions with a fast camera. Numerical simulation studies have also started in the end-cell for understanding the behavior of plasmas in divertor simulation experiments. In this spring a large-sized divertor experimental module will be installed and radiative cooling experiments of the end-cell plasma are planned by using gas injection into the module for realizing the detached plasma condition.

[1] Y. Nakashima, et al., Fusion Eng. Design volume 85 issue 6 (2010) 956-962.

[2] Y. Nakashima, et al., Trans. Fusion Sci. Technol. 59 No.1T (2011) 61-66.

This work is supported by the bidirectional collaboration research program with National Institute for Fusion Science.

Country or International Organization of Primary Author

Japan

Primary author: Mr NAKASHIMA, Yousuke (Japan)

Co-authors: Prof. SAGARA, Akio (National Institute for Fusion Science); Prof. TONEGAWA, Akira (Graduate school of Science, Tokai University); Prof. HATAYAMA, Akiyoshi (Faculty of Science and Technology, Keio University); Mr UEDA, Hideaki (Plasma Research Center, University of Tsukuba); Dr MATSUURA, Hiroto (Radiation Research Center, Osaka Prefecture University); Mr TAKEDA, Hisato (Plasma Research Center, University of Tsukuba); Prof. KATANUMA, Isao (University of Tsukuba); Dr KOHAGURA, Junko (Plasma Research Center, University of Tsukuba); Mr HOSOI, Katsuhiko (Plasma Research Center, University of Tsukuba); Mr ICHIMURA,

Kazuya (Plasma Research Center, University of Tsukuba); Dr HIRATA, Mafumi (Plasma Research Center, University of Tsukuba); Prof. ICHIMURA, Makoto (Plasma Research Center, University of Tsukuba); Dr SHOJI, Mamoru (National Institute for Fusion Science); Dr YOSHIKAWA, Masayuki (University of Tsukuba); Mr TOMA, Mitsunori (Faculty of Science and Technology, Keio University); Prof. SAKAMOTO, Mizuki (Plasma Research Center, University of Tsukuba); Dr NISHINO, Nobuhiro (Graduate school of Engineering, Hiroshima University); Dr ASAKURA, Nobuyuki (Japan Atomic Energy Agency); Prof. OHNO, Noriyasu (Graduate school of Engineering, Nagoya University); Dr MINAMI, Ryutaro (Plasma Research Center, University of Tsukuba); Dr IKEZOE, Ryuuya (Plasma Research Center, University of Tsukuba); Dr NAGATA, Shinji (Institute for Material Research, Tohoku University); Dr KADO, Shinnichiro (Department of Nuclear Engineering and Management, The University of Tokyo); Dr MASUZAKI, Suguru (National Institute for Fusion Science); Prof. SHIKAMA, Tatsuo (Institute for Material Research, Tohoku University); Mr FURUTA, Tetsuo (Faculty of Science and Technology, Keio University); Dr NUMAKURA, Tomoharu (Plasma Research Center, University of Tsukuba); Prof. IMAI, Tsuyoshi (Plasma Research Center, University of Tsukuba); Dr KARIYA, Tsuyoshi (Plasma Research Center, University of Tsukuba); Prof. HIROOKA, Yoshihiko (National Institute for Fusion Science); Prof. UEDA, Yoshio (Graduate school of Engineering, Osaka University)

Presenter: Mr NAKASHIMA, Yousuke (Japan)

Session Classification: Poster: P1

Track Classification: FTP - Fusion Technology and Power Plant Design