

# International Conference on Fast Reactors and Related Fuel Cycles: Next Generation Nuclear Systems for Sustainable Development (FR17)



Contribution ID: 322

Type: POSTER

## Optimization of the thermomechanical treatment to achieve a homogeneous microstructure in a 14Cr ODS steel

*Tuesday, June 27, 2017 5:30 PM (1h 30m)*

Oxide dispersion strengthened (ODS) ferritic steels are promising candidates for high burn up fuel pins of Sodium Fast Reactors. They are elaborated by powder metallurgy and their manufacturing route is complex and specific, including hot forming and cold working. Different heat treatments are necessary to recrystallize these materials and to relieve internal stresses. The presence of highly stable nano-oxides and the limited stored energy after elaboration can make the recrystallization temperature extremely high ( $> 0.9 T_{\text{melting}}$ ). The aim of this paper is to present the results of a generic study conducted on the recrystallization mechanisms in ODS materials. Model alloys with specific deformations by cold working were studied. It comes out that the direction along which the samples are deformed is determining to increase the driving force for recrystallization and obtain homogeneous microstructures, more than the rate of cold-working applied.

### Country/Int. Organization

France/Commissariat à l'énergie atomique

**Primary author:** Mr HARY, Benjamin (CEA)

**Co-authors:** Prof. LOGÉ, Roland (EPFL); Dr BAUDIN, Thierry (Université Paris-Sud); Dr DE CARLAN, Yann (CEA)

**Presenter:** Mr HARY, Benjamin (CEA)

**Session Classification:** Poster Session 1

**Track Classification:** Track 5. Fast Reactor Materials (Fuels and Structures) and Technology