

# Effect of sorbent selection and geometrical arrangement of cryopanel on pumping speed of cryopump

Wednesday, October 24, 2018 8:30 AM (20 minutes)

Vacuum is an inherent part of any Fusion machine. The requirement of providing large pumping speed is growing as fusion science is progressing towards high temperature, high density, and large confinement machines. In its domestic programme of development of technologies for Fusion grade machines, Institute for Plasma research (IPR) developed the sorbent based cryopumps. Using coconut shell charcoal pumping speed of 2 l/s/cm<sup>2</sup> for helium and 5 l/s/cm<sup>2</sup> for hydrogen is demonstrated. Different sorbents are under study for their performance of pumping speed, for example carbon cloth and flocked carbon panels. Experimental study of pumping speed is being carried for different geometrical configurations of panel arrangements. MOLFLOW+ is used for simulating the pumping speed. Initial experiments are being carried out at 80 K and compared with MOLFLOW+ results. This paper discusses in detail simulation and experimental results of developed pumps

## Country or International Organization

India

## Paper Number

FIP/P3-54

**Primary author:** Ms GANGRADEY, Ranjana (Institute for Plasma Research)

**Co-authors:** Ms AGARWAL, Jyoti (Institute for Plasma Research); Dr JYOTI SHANKAR, Mishra (Institute for plasma research); Mr PANCHAL, Paresh (Institute for plasma research); Mr NAYAK, Pratik (Institute for plasma research); Mr MUKHERJEE, Samiran Shanti (Institute for Plasma Research); Mr DAS, Subhadip (Institute for plasma research); Mr GUPTA, Vishal (Institute for plasma research)

**Presenter:** Ms GANGRADEY, Ranjana (Institute for Plasma Research)

**Session Classification:** P3 Posters

**Track Classification:** FIP - Fusion Engineering, Integration and Power Plant Design