

# Demonstration of 1 MV vacuum insulation for the vacuum insulated beam source in the ITER NB system

Monday, October 22, 2018 5:35 PM (5 minutes)

For the ITER neutral beam (NB) system, a measure to achieve the 1 MV vacuum insulation of the beam source have been developed. For this purpose, design basis for 1 MV vacuum insulation has been developed by integrating previous empirical scaling for plane and coaxial electrodes and new scaling for area with locally-concentrated electric field. Consequently, as the measure, the beam source is surrounded by more than three intermediate electrostatic shields instead of single gap to sustain 1 MV. Effectiveness of the shields designed by the design basis was experimentally verified by using a part of the beam source. The voltage holding capability has been significantly improved from 0.7 MV to 1 MV. This result ensures the 1 MV vacuum insulated beam source in the ITER NB system.

## Country or International Organization

Japan

## Paper Number

FIP/1-3Rc

**Primary author:** Mr KOJIMA, Atsushi (National Institutes for Quantum and Radiological Science and Technology)

**Co-authors:** Mr LARRY, Grisham (PPPL); Mr YAMANAKA, Haruhiko (QST); Dr TOBARI, Hiroyuki (QST); Dr HIRATSUKA, JUNICHI (National Institutes for Quantum and Radiological Science and Technology); Mr WATANABE, Kazuhiro (QST); Mr ICHIKAWA, Masahiro (QST); Mr DAIRAKU, Masayuki (QST); Ms KASHIWAGI, Mieko (QST); Mr SHIBATA, Naoki (QST); Mr UMEDA, Naotaka (National Institutes for Quantum and Radiological Science and Technology); Mr YAMASHITA, Yasuo (QST); Mr YAMANO, Yasushi (Saitama University)

**Presenter:** Mr JOSHI, Jaydeepkumar (ITER-India (Institute for Plasma Research))

**Session Classification:** FIP/1 ITER Technology

**Track Classification:** FIP - Fusion Engineering, Integration and Power Plant Design