

# Liquid DT Layer Approach to Inertial Confinement Fusion

Wednesday, October 24, 2018 9:10 AM (20 minutes)

The baseline approach to high gain ICF involves the implosion of capsules containing a layer of DT ice [1]. DT ice layer designs require a high convergence ratio ( $CR > 30$ ) implosion, with a hot spot that is dynamically created from DT mass originally residing in a thin layer at the inner DT ice surface. Although high CR is desirable in an idealized 1D sense, it amplifies the deleterious effects of realistic features and asymmetries [2]. An alternative ICF concept uses DT liquid layers [3]. DT liquid layers allow for much higher vapor densities than are possible with DT ice layers. The wide range of vapor densities that are possible with DT liquid layers provides flexibility in hot-spot CR ( $12 < CR < 25$ ), which, in turn, will provide a reduced sensitivity to asymmetries and instability growth. Given enough vapor mass, the hot spot can be formed from the mass originally residing in the central vapor region. Recent experiments at the National Ignition Facility (NIF) have demonstrated cryogenic liquid DT layer ICF implosions, along with the associated flexibility in the hot spot CR [4,5].

There are tradeoffs involved in high CR ice layer and reduced CR liquid layer designs. With reduced CR, hot spot formation is expected to have improved robustness to instabilities and asymmetries [2-5]. In addition, the hot spot pressure ( $P_r$ ) required for self-heating is reduced if the hot spot radius ( $R_{hs}$ ) is increased ( $P_r \propto R_{hs}^{-1}$ ). With a reduction in the hot spot  $P_r$  requirement, the implosion velocity and fuel adiabat requirements are relaxed. On the other hand, with larger hot spot size, the hot spot energy requirement for self-heating ( $E_{hs}$ ) is increased ( $E_{hs} \propto R_{hs}^2$ ), and the required capsule absorbed energy is increased. In this presentation, we will summarize the recent liquid layer experiments at the NIF and will discuss the hot spot energy, hot spot pressure, cold fuel adiabat, and capsule-absorbed energy requirements for achieving self-heating and propagating burn using liquid layer capsules with hot spot  $CR < 20$ .

## References

- [1] S. W. Haan et al., Phys. Plasmas 18, 051001 (2011).
- [2] B. M. Haines et al., Phys. Plasmas 24, 072709 (2017).
- [3] R. E. Olson and R. J. Leeper, Phys. Plasmas 20, 092705 (2013).
- [4] R. E. Olson et al., Phys. Rev. Lett. 117, 245001 (2016).
- [5] A. B. Zylstra et al., Phys. Plasmas, to be published (2018).

## Country or International Organization

United States of America

## Paper Number

IFE/1-3

**Primary author:** Dr OLSON, Rick (Los Alamos National Lab)

**Co-author:** Dr LEEPER, Ray (Los Alamos National Lab)

**Presenter:** Dr LEEPER, Ray (Los Alamos National Lab)

**Session Classification:** IFE/1 Inertial Fusion Experiments & Theory

**Track Classification:** IFE - Inertial Fusion Experiments and Theory