



Contribution ID: 155

Type: Poster

Increasing plutonium disposition rate in the thermal reactors (VVER and RBMK)

Wednesday, 26 June 2019 10:45 (15 minutes)

Several countries reuse MOX fuel (reactor-grade (RG) and weapons-grade (WG) Pu) in the thermal reactors, but within no more than 30% of the total core loading. Many years of operational experience with MOX-fuelled cores along with well-developed technologies in the management of MOX fuel demonstrate possibilities in extending MOX fuel share in commercial nuclear power plants. Therefore, this paper deals increasing weapons-grade plutonium disposition rate (mPu) in the thermal reactors using differenced methods as: reducing the burnup, reducing the residence time of the MOX assemblies in the reactor, increasing the fraction of MOX assemblies in the core, and reducing the plutonium enrichment in the MOX fuel. The results showed at EOC for 100% MOX fuel that the mPu were: 1320 and 930 kg/year and the ^{240}Pu fractions were: 31 and 45% for VVER and RBMK respectively. The mPu was increased: 930, 985, 1076 and 1590 when the plutonium enrichment was reduced: 1.8, 1.6, 1.4, 1.0 % respectively. The mPu was increased by 45% when using four UO₂ fuel cycles and one MOX cycle instead of three UO₂ fuel cycles and one MOX cycle.

Do you wish to enter the YGE SFM19 Challenge?

Country or International Organization

Syrian Arab Republic

Primary author: Dr ALDAWAHRAH, Saadou (Syrian atomic energy commission)

Presenter: Dr ALDAWAHRAH, Saadou (Syrian atomic energy commission)

Session Classification: Track 4 Poster Session

Track Classification: Track 4: Recycling as a spent fuel management option