



Methodology Development for Characterization in the Field of NORM Originating from Oil Industries by using a LaBr₃(Ce) Scintillator

Methodology Development for Characterization in the Field of NORM Originating from Oil Industries by using a LaBr₃(Ce) Scintillator

The last decade LaBr₃(Ce) scintillation detectors have become commercially available and are very promising due to their high light yield (> 65000 photons/MeV) that results in a better energy resolution compared to NaI(Tl) detectors (< 3% FWHM at 137Cs), their decay time of 35 ns and their material density (5.29 g/cm³) [1, 2]. Also, there is no need for cooling comparing to HPGe detectors. Thus, LaBr₃(Ce) detectors could be a suitable choice for environmental radiation monitoring [3] and in-situ measurements of NORM [4].

Gamma spectrometry measurements and MCNP-X simulations were combined for the in-situ technique development. Factors that affect NORM analysis, such as LaBr₃(Ce) internal background, detector efficiency and peak interferences, were considered in order to select the optimal NORM radionuclides from uranium and thorium radioactive series and the corresponding emitting peak energies that will be used for the measurements. The activities of other radionuclides in the series, in radioactive equilibrium with the measured ones, can be estimated. The detector efficiency calibration was evaluated by MCNP-X simulations after taking into consideration common NORM waste geometries originating from Oil Industries. Minimum detectable activities for the selected radionuclides were also determined. The radionuclides which are not possible to be determined based on gamma spectrometry were identified for sampling and radiochemical analyses, if needed. Then, NORM gamma spectrometry characterization measurements were performed by using the LaBr₃(Ce) in the field.

This methodology can be effectively applied at Oil Industries for the fast and cost effective radiological characterization of NORM waste.

This study is supported by the program of Industrial Scholarships of Stavros Niarchos Foundation.

[1] Knoll G. F., John Wiley and Sons, 1999.

[2] Quarati, F., Bos, A.J.J., Brandenburg, S., Dathy, C., Dorenbos, P., Kraft, S., Ostendorf, R.W., Ouspenski, V., Owens, A. 2007. X-ray and gamma-ray response of a 2' x 2' LaBr₃:Ce. Nucl. Instr. Meth. Phys. Res. A 574, 115-120.

[3] Ciupek, K., Jednoróg, S., Fujak, M., Szewczak, K. 2014. Evaluation of efficiency for in situ gamma spectrometer based upon cerium-doped lanthanum bromide detector dedicated for environmental radiation monitoring. J. Radioanal. Nucl. Chem. 299, 1345-1350.

[4] Mueller, W. F., Ilie, G., Lange, H.J., Rotty, M., Russ, W.R. 2013. In-situ measurements and analysis of naturally occurring radioactive materials. ANIMMA paper #1310

Primary authors: Ms NTALLA, Eleni (Institute of Nuclear & Radiological Sciences & Technology, Energy & Safety, National Center for Scientific Research "Demokritos"); Mr CLOUVAS, Alexandros (Department of Electrical and Computer Engineering, Aristotle University of Thessaloniki); SAVIDOU, Anastasia (Institute of Nuclear & Radiological Sciences & Technology, Energy & Safety, National Center for Scientific Research "Demokritos")

Presenter: Ms NTALLA, Eleni (Institute of Nuclear & Radiological Sciences & Technology, Energy & Safety, National Center for Scientific Research "Demokritos")

Session Classification: Session IV - Characterization in Industrial Facilities and in the Environment

Track Classification: NORM Characterization, Measurement, Decontamination