



# COMPLETION OF THE FIRST ITER TOROIDAL FIELD COIL IN JAPAN

M. NAKAMOTO, T. BABA, Y. KASAI, K. SAKAMOTO, H. SHIMANE, T. SHIMIZU,  
K. SAITO, M. NAKAHIRA, N. KOIZUMI (QST)  
M. INOUE, E. FUJIWARA, T. SHICHIJO (MHI)  
K. KUNO, M. YAMANE, M. HASEGAWA (MELCO)  
C. LUONGO (IO)

11<sup>th</sup> May 2021  
28<sup>th</sup> IAEA Fusion Energy Conference  
Virtual/Nice, France

- 18 Toroidal Field Coils (TFC) in ITER
- TFC Specifications
  - Peak magnetic field: 11.8 T
  - Total magnetic energy: 41 GJ
  - Conductor material: Niobium Tin ( $Nb_3Sn$ ), with application temperature  $\sim 4$  K
  - TFC material: SS316LN – ITER grade to maintain the structural integrity at 4 K, not easy to control welding deformation.



TFCs are indicated in red.

- ITER TFC is the largest  $Nb_3Sn$  magnets in the world.
- Completion of the 1<sup>st</sup>-of-a-kind ITER TFC is an important milestone in the fusion energy research field.

**Function of 18 TFC: to generate precise circular magnetic field in a vacuum vessel**

Magnetic property of whole TFC system

**Assemblability:**  
Precise positioning of 18 TFCs


**Magnetic property:**  
Common among TFCs

Magnetic property of each TFC

**Interface tolerances**

**CCL tolerances on each TFC**

**Min. Gap**



IOIS: **2 mm** profile



OIS: **0.5 mm** flatness

IIS: **Φ2 mm** positional

ILIS: **0.4 mm** profile

**≤ ± 3 mm**  
@ outboard

**≤ φ2.6 mm**  
@ inboard




**4 mm** everywhere, for complete gap-filling




**Control of deviations during assembly is necessary.**


# 1.3 Introduction: TFC assembly steps




**WP Insertion**



**Outboard Insertion**



**TFCs Welding**



**Final Machining**



**Gap-filling**

**Final Inspection**




**Any misalignments or welding deformations would be compensated by Final Machining.**



## A) Interfaces

**Issue:** welding deformation control  
 ⇒ **Solution 1:** In-advance estimation of welding deformation (trials, FEM structural analysis) & extra materials to be finished at final machining (described in 3.1)  
 ⇒ **Solution 2:** Harmonization as remedial action in case of large deformation (described in 3.2 & 3.3)



## B) Gap

**Issue 1:** High viscosity resin injection into narrow gap (described in 4.1)  
**Issue 2:** Maintaining 4 mm gaps through welding  
 ⇒ **Solution:** establishment of the resin injection method into gaps < 4 mm (described in 4.2)

## C) CCL

**Issue 1:** Precise positioning of WP within TFCS  
**Issue 2:** Maintaining WP shape/positions through fabrication  
 ⇒ **Solution 1:** In-advance assessment of target WP position & monitoring w/ laser tracker (described in 5.1)  
**Solution 2:** Traceability measurements & updating CCL information (described in 5.2)

**Welding qualification trials** Local analysis

Inherent strain parameters

**FEM analysis** Global analysis


**Actual coil**

Extra materials -> machined later  
Laser tracker monitoring -> adjustment

### Comparison of welding deformation



	Trial	FEM	1 <sup>st</sup> coil
A1	8	5.6	6.9
A2	3.11	0	2.2
B1	4.4	4.0	5.0
C1	3.9	3.5	5.0
C2	3.6	2	1.8
C3	3.90	2	3.2

Unit: mm




**The distortions on interfaces were within the extra materials except at IOIS.**

- **A few mm lack of materials at IOIS interfaces on outboard.**
  - 14.4 mm max. distortion
  - 10 mm extra materials + 2 mm profile tolerance
- **Comparison** to welding deformation results between EUDA's 1<sup>st</sup> coil & JADA's 1<sup>st</sup> coil:
  - **The common trends** were observed.
- **Harmonization:**
  - **18 TFCs can be assembled** if all have the same shape
  - **Global remedial action** to accept the welding deformation
  - guided by IO




**All the interfaces satisfied the severe tolerances.**

- Interface: sub-millimeter tolerances to secure assemblability of TFCs
- Interface measurement results of succeeding TFCs after welding:



Deviations from nominal after welding



With extra materials



Machined to nominal during Final Machining.



**For the 1<sup>st</sup> TFC,**  
 - Interface tolerances: satisfied!  
 - Assemblability: ensured!




- Gap-filling:
  - **Structural integration** of a WP and a TFCS (compressive strength, integrated thermal contraction)
  - Satisfaction of structural requirements resulted in **High viscosity resin** (10 Pa·s for fresh mix, 26 Pa·s after 24 hrs)
  - **Fiberglass layer** on WPs
  - **Vacuum pressure impregnation** to prevent void formation (0.2MPa pressurization).
- **Min. gap:** 4 mm to ensure the complete filling of gap with high viscosity resin.
- **Fresh resin at the resin front:** to minimize void formation & valves for higher resin injection holes were opened as the resin level reaches the hole positions.





Verification of gap-filling procedure with those measures is necessary.

- Resin injection trials to establish a resin injection method:
  - High viscosity resin
  - for narrow gaps (<4 mm) due to larger welding deformation



**Local gap of 2 mm: Acceptable w/ improved procedure!**


- In-advance assessment of target WP position optimizing CCL positions while keeping 4 mm gap.




Gap analysis

Welding deformation expectation

Ideal case



Realistic case



Inclination of outboard during welding  $\leq \pm 3$  mm

WP tilt adjustment  
 $\Rightarrow$  gap  $\geq 4$  mm



- Optimized WP target position from gap analysis
- Laser tracker monitoring for fine adjustment of 0.1mm order

- **CCL traceability measurements** by laser tracker:
  - Frequent measurements  $\Rightarrow$  **minimize errors** during final machining
  - Repetitive measurements  $\Rightarrow$  **minimize uncertainties**
- **Original measurement plan**
  - up to cover installation of TFCS.
  - At CCL cross sections



Laser tracker measurement

**A concern of welding deformation impact on WP shape/position from IO**


- **Additional measurement plan**
  - Up to gap-filling
  - At resin injection holes after cover installation
  - Use of structural analysis for CCL calculation

**CCL deviations:**


- 0.35 mm max. @ inboard
- 1.46 mm max. @ outboard

**CCL requirements: satisfied!**


Resin injection holes, V1-V9 & CCL cross sections, A-H





- **Interface requirement: satisfied!**  
(tolerances are indicated with dot-line boxes.)



- **CCL position requirement: satisfied!**  
(uncertainty range is shown with bars.)



- **Min gap requirement: satisfied!**



For the 1<sup>st</sup> TFC,  
- Magnetic property: achieved!  
- Assemblability: achieved!



- The world's first ITER TFC was manufactured in Japan in January 2020, satisfying requirements.
- Completion of the 1<sup>st</sup>-of-a-kind was celebrated by holding a ceremony at MHI premises (Kobe, Japan).
- 3 TFCs from EUDA & 3 TFCs from JADA were delivered to ITER.





