

RMP induced H-mode transition during divertor detachment with enhanced edge radiation in deuterium plasmas in LHD

M. Kobayashi, R. Seki, Y. Takemura, Y. Oishi, K. Tanaka, K. Mukai, S. Morita, K. Ida, S. Masuzaki, and the LHD Experiment Group
National Institute for Fusion Science
kobayashi.masahiro@nifs.ac.jp

Compatibility of good core plasma performance with divertor heat load mitigation

ETB & impurity radiation (detachment) are compatible each other? If so, how they interact each other?

Bifurcation of detachment
 $P_{loss} = q_{trans} + P_{rad}$
 Stable (Attach) / Unstable (Detach)
 $q_{trans} = \kappa_e T_e^{2.5} \nabla T_e$
 $P_{rad} = n_e n_i \sigma_{ei} L(T)$

Bifurcation of ETB
 Adiabaticity parameter: Ratio of i -electron diffusion speed and turbulence propagation speed
 $\alpha_{adi} = \frac{K_{eff} v_{the}}{|\omega| v_{ei}} \propto T_e^2 / n$
 $T_e \uparrow \rightarrow \alpha_{adi} \uparrow \rightarrow$ collapse of shear layer (Zonal flow)
 Hajjar PoP 2018

Resistive pressure gradient driven MHD instability:
 $\gamma_{interchange} \propto \eta^{1/2} L_p^{-2/3} \propto L_p^{-2/3} T_e^{-0.5}$
 $T_e \uparrow \rightarrow \alpha_{adi} \uparrow \rightarrow$ Drift resistive MHD transport enhanced
 $\alpha_{dia} \propto D_{Di} / D_{D0}$ Rogers PRL 1998

Detachment needs low T_e at the edge → Compatible? → Low edge T_e degrades ETB

Change of edge magnetic field structure for study on compatibility of confinement with detachment

RMP application → Sharp boundary btw confinement region and stochastic layer

Without RMP
 Intrinsic edge stochastic layer
 Gradual increase in L_c toward confinement region → no ETB formation

With RMP
 Stochastic layer widened → Increased impurity radiation volume
 Sharp boundary between confinement and edge region → ETB formation

Edge magnetic structure/topology impacts on radiation enhancement & core confinement (Compatibility of ETB with cold edge plasma with impurity radiation)

Impact of RMP on density limit, radiated power, and global energy confinement

Density ramp-up discharges with & without RMP application
 ✓ Detachment is induced with density ramp-up, NBI is kept constant at ~5MW
 ✓ Main radiator is carbon from divertor plate. No impurity seeding.

Change of edge magnetic field structure/topology resulted in significant difference in core and divertor performance.
 With RMP → Higher density, higher radiation (stable detachment), higher confinement (confinement mode transition, ETB formation).
 Edge magnetic structure plays a key role on compatibility of confinement and radiation enhancement

Impact of RMP on edge plasma parameter profiles: Edge transport barrier at confinement boundary

Without RMP:
 Smooth radial decay of T_e and n_e
 → Shrinkage of profiles with high density → radiation collapse

With RMP:
 At low density (Attached phase) Sharp gradient in T_e at confinement boundary
 n_e is flat
 At detachment Sharp gradient in both T_e and n_e at confinement boundary → ETB formation

Edge impurity radiation distribution obtained by 2D imaging spectroscopy

Without RMP
 Attached phase: impurity emission along divertor leg
 With increasing density, impurity emission penetrates confinement region → collapse.

With RMP
 Attached phase: impurity emission along divertor leg
 Detached phase: impurity emission moves toward confinement region → Stops at boundary
 Blocking of radiation penetration by ETB (?)
 CIII shows similar behavior

Confinement mode transitions in detachment with RMP (m/n=1/1) application

Detachment is induced with density ramp-up, NBI is kept constant at ~5MW
 ✓ Main radiator is carbon from divertor plate. No impurity seeding
 ✓ Detached at ~3.95 sec (reduction of div particle flux)
 ✓ Discharges are sustained up to density limit (n_{lim})
 ✓ Spontaneous increase of W_p occurs at ~3.95 and 4.55 sec during detached phase → Reduction of density fluctuation → ELM-like spikes in B_z and div particle flux
 ✓ ETB developed at inner edge of island induced by RMP

Interaction between edge cooling, ETB, and core transport: MHD activity degrades ETB → fluctuation increase → confinement mode transition

As the detachment deepens, the edge T_e decreases due to impurity radiation → resistivity increases
 $\gamma_{interchange} \propto \eta^{1/2} L_p^{-2/3} \propto L_p^{-2/3} T_e^{-0.5}$

MHD activity is excited by pressure gradient at ETB (m/n=3/3)
 Pressure gradient at ETB collapses → W_p increase stops

Core transport responds to compensate degradation of ETB → W_p kept constant during MHD activity

Interaction between edge cooling, ETB, and core transport: MHD activity degrades ETB → fluctuation increase → confinement mode transition

As the detachment deepens, the edge T_e decreases due to impurity radiation → resistivity increases
 $\gamma_{interchange} \propto \eta^{1/2} L_p^{-2/3} \propto L_p^{-2/3} T_e^{-0.5}$

MHD activity is excited by pressure gradient at ETB (m/n=3/3)
 Pressure gradient at ETB collapses → W_p increase stops

Gradual increase of density fluctuation (~30kHz)
 → Spontaneous recovery of ETB and increase of W_p resumes at ~4.5 sec → Fluctuation decreases, ELM starts
 Adiabaticity still high > 1 ← ETB branch maintained

With RMP, including radiation collapse shots
 Transition possible

At operation limit: $\alpha_{adi} \leq 1, \alpha_{adi} \leq 1$
 → both DW & DRB turbulence responsible

Development of pedestal during confinement mode transition and τ_E scaling

1. After detachment transition, development of pedestal with density increase
 ← Similar to standard H-mode transition

2. Degradation due to MHD activity occurs with T_e decrease

3. Confinement improvement proceeds with increase of T_{ped}

Confinement sustained at higher density with RMP application ← Due to ETB formation
 Confinement improvement significantly deviates from gyro-Bohm scaling

Divertor heat load pattern in toroidal direction with RMP application: Attached & detached phases

Attached phase: Divertor heat load is modulated in toroidal direction (n=1 mode) with RMP
 Detached phase: Divertor heat load is decreased at all section with RMP by ~70% on avg.
 Slight increase observed at 2L & 10R during detached phase
 ← Still lower than the case without RMP

Field line trace of 6L probe (3 toroidal turns)
 Flux tubes connected near X-point

Field line trace of 10R probe (3 toroidal turns)
 Flux tubes connected near O-point

Field line tracing of divertor foot point: 10R (2L) are connected near island O-point
 Others are connected near X-point (away from O-point)
 O-point is less cooled down compared to X-point (?)

→ In the next experiments, impurity seeding is tried to cool down 10R & 2L sections further.

Divertor peak heat load slightly returns during improved mode

Divertor heat load increases during the improved mode. Due to decrease in P_{rad} (decontamination during improved mode) and to ELM pulses.
 (heat load is time-averaged during & inter-ELM phase)
 → Reduction of heat load is tried with impurity seeding in next experiments

Other sections remains low

Summary

Role of edge magnetic field structure/topology on detachment and compatibility with core plasma confinement is being investigated in LHD.

- Sharp boundary between confinement region and stochastic layer can be introduced with RMP (m/n=1/1) application
 ETB formation at detachment onset → Higher density, higher radiated power, better confinement are achieved
 Cold front propagation stopped at the confinement boundary (at ETB)
 Core transport is similar level with and without RMP, except for the ETB formation in RMP case
 ETB is stronger in deuterium plasmas than hydrogen plasmas
- Confinement mode transition occurs with RMP application during detached phase (in deuterium):
 2.1 ETB formation at detachment onset
 2.2 Interplay between edge cooling, MHD activity, and ETB during detachment
 Detachment deepens / Edge T_e decreases → Resistive pressure gradient driven MHD mode excited → ETB collapsed, but core transport responds to compensate degradation of ETB
 → Fluctuation increase → sudden recovery of ETB and confinement improvement
 Compatibility of confinement mode transition with cold edge plasma possible ($\alpha_{adi} > 1$)
 Operation limit at $\alpha_{adi} \leq 1, \alpha_{adi} \leq 1$ → both DW & DRB turbulence responsible
- Divertor heat load decreases during detached phase with RMP by 70% on average
 n = 1 mode structure in attached phase → Spatial phase shift of heat load at detached phase
 At certain sections, slight increase is observed. (heat load is already low at attached phase by RMP application)
 These sections are connected near O-point.
 Slight increase during improved mode due to decrease of P_{rad} (impurity decontamination) and ELMs

Key role of edge magnetic field structure: Enhancement of radiation with increased low T_e volume, ETB formation at sharp boundary