



# PLASMA-SURFACE INTERACTIONS IN THE STELLARATOR W7-X: CONCLUSIONS DRAWN FROM OPERATION WITH GRAPHITE PLASMA-FACING COMPONENTS

S. Brezinsek<sup>1</sup>, C.P. Dhard<sup>2</sup>, M. Jakubowski<sup>2</sup>, R. König<sup>2</sup>, S. Masuzaki<sup>3</sup>, M. Mayer<sup>4</sup>, D. Naujoks<sup>2</sup>, J. Romazanov<sup>1</sup>, K. Schmid<sup>4</sup>, O. Schmitz<sup>5</sup>, D. Zhao<sup>1</sup>, M. Balden<sup>4</sup>, R. Brakel<sup>2</sup>, B. Butterschön<sup>2</sup>, T. Dittmar<sup>1</sup>, P. Drews<sup>1</sup>, F. Effenberg<sup>5</sup>, E. Fortuna-Zalesna<sup>6</sup>, Y. Gao<sup>7</sup>, A. Gorjaev<sup>7</sup>, A. Hakola<sup>8</sup>, T. Kremeyer<sup>2</sup>, M. Krychowiak<sup>2</sup>, G. Motojima<sup>3</sup>, R. Neu<sup>4</sup>, J. Olemann<sup>1</sup>, O. Neubauer<sup>1</sup>, P. Petersson<sup>8</sup>, M. Rasinski<sup>1</sup>, M. Rubel<sup>8</sup>, S. Sereda<sup>1</sup>, E. Wang<sup>1</sup>, T. Wauters<sup>7</sup>, V. Winters<sup>2</sup>, R. Yi<sup>1</sup> & W7-X team

<sup>1</sup>Forschungszentrum Jülich, Institut für Energie- und Klimaforschung – Plasmaphysik, 52425 Jülich, Germany | <sup>2</sup>Max-Planck-Institut für Plasmaphysik, 17491 Greifswald, Germany | <sup>3</sup>National Institute for Fusion Science, Toki, Japan | <sup>4</sup>Max-Planck-Institut für Plasmaphysik, D-85748 Garching, Germany | <sup>5</sup>University of Wisconsin - Madison, Engineering Physics, Madison, WI 53706, USA | <sup>6</sup>Warsaw University of Technology, 02-507 Warsaw, Poland | <sup>7</sup>Laboratory for Plasma Physics, LPP-ERM/KMS, B-1000 Brussels, Belgium | <sup>8</sup>VTT P.O.Box 1000, 02044 VTT, Finland | <sup>9</sup>Royal Institute of Technology (KTH), Se-10044 Stockholm, Sweden


## Introduction to the Optimised Stellarator Wendelstein 7-X

- Optimised stellarator design with 5-fold symmetry
- Magnetic field: 2.5 T (steady-state)
- Heating power: 7.5 MW ECRH / 3.4 MW NBI
- Major Radius: 5.5 m / Minor Radius: 0.53 m
- Island divertor for power and particle exhaust and impurity screening
- Divertor target plates follow the magnetic islands geometry



- attached and detached divertor operation executed in 2 campaigns
- OP A: ~3776 s (He+H plasma) | OP B: ~9054 s (~H plasma)
- max. plasma duration: 100 s | max. input energy: 0.2 GJ
- at the strike line in attached plasmas:  $T_e \sim 25$  eV |  $n_e \sim 1.0 \times 10^{19}$  m<sup>-3</sup>


Can we interpret the plasma-wall interactions in W7-X?  
What can be expected for 30 min. plasmas with actively cooled divertor?  
Recommendations regarding the divertor operational regime?



## Plasma-Facing Components in W7-X


- Island Divertor with Test Divertor Unit (TDU)
  - 5 modules with 2 halves
  - Divertor material: fine grain graphite
  - Divertor area: 19 (25) m<sup>2</sup>
  - Max. divertor heat load: 10 MW/m<sup>2</sup>
  - No active cooling at this stage

- First wall coverage (FW)
  - Main FW wall area: 45 m<sup>2</sup> with C
    - 15 m<sup>2</sup> up to 0.5 MW/m<sup>2</sup>
    - 30 m<sup>2</sup> up to 0.25 MW/m<sup>2</sup>
  - Recessed wall area: 70 m<sup>2</sup> with SS
    - 70 m<sup>2</sup> up to 0.2 MW/m<sup>2</sup>
  - Nominal wall temperature: RT






C. P. Dhard et al. 2020 Phys. Scr. T171 014033

## Plasma-Wall Interactions Processes



## Erosion / Deposition Measurements Utilising Marker Divertor Target Elements


Multiple divertor target elements with Mo interlayer and C marker for net erosion / deposition information installed per campaign. 2 locations on the vertical and 3 locations on the horizontal target plate in each of the ten half modules.



OP A: complete erosion of C marker and Mo interlayer and peak erosion zones only due to oxygen and carbon ions


## Impact of Boronisation on W7-X Operation in OP B

- Initial plasma operation (OP A) compromised by high impurity content (O, C) and H outgassing
- residual water in graphite released during PFC heat-up by plasma impact
- physical and chemical sputtering of graphite by O and H as well as C self sputtering
- oxide layers on first wall sputtered by plasma and charge exchange neutrals
- oxygen partially pumped out between discharges in form of CO and CO<sub>2</sub>




- 3 boronisations via (He+B<sub>2</sub>H<sub>6</sub> GDC) applied in OP B
- strong reduction of O influx and content (gettering effect)
- break of O cycle in plasma | reduction of C sputtering by O
- transient reduction of C influx and content in plasma
- long-lasting effect: first wall components coverage
- short-lasting effect: transient divertor surface coverage

## Netto Erosion / Deposition Measurements at the Horizontal Target Plates



- net C erosion via EBS measured
- campaign integrated information
- peak erosion at strike-line
- up-down erosion variations
- Mo interlayer erosion at some half modules due to C and O
- toroidal asymmetry in C erosion reflects heat load asymmetry
- Mo erosion used as proxy for C
- reduction of C and Mo erosion in OP B after boronisation
- erosion rate drops by factor 6-8


## Netto Erosion / Deposition Measurements at the Vertical Target Plates





- Reduction of C erosion after boronisation only a factor 3 at this location
- Erosion of Mo interlayer continues
- Strong local deposition zone towards baffle
- ps-LIBS analysis reveals composition
- Mixture of B, C, O, H and Fe in deposition
- Fe due to He-GDC on boronisation
- No H at peak erosion zone

## 3D Simulation of Material Migration in Standard Configuration with ERO2.0

- significant operation in standard configuration (>50%: 4809 s)
- main interaction area almost unique for this magnetic configuration
- representative hydrogen plasma background from EMC3-EIRENE reference attached divertor plasma with C as main impurity (from <sup>13</sup>CH<sub>4</sub>)



- 3D simulation of PSI with ERO2.0 of one W7-X module:
  - periodic boundary conditions of fivefold symmetry to mimic full device
  - Unfold C gross erosion and C deposition pattern in the divertor
  - C net erosion and net deposition areas are located close to each other at the strike-line location in standard configuration
  - Comparison with post-mortem analysis (net) and C spectroscopy (gross)




Main characteristics reproduced and good quantitative agreement of peak erosion, but re-deposition underestimated in ERO

## 3D Simulation of <sup>13</sup>C Migration in Standard Configuration with WallDYN-3D

- benchmark experiment about C transport in a full-C device is a <sup>13</sup>CH<sub>4</sub> injection
- last experiment in OP B before tile removal
- 4.5x10<sup>21</sup> <sup>13</sup>C injected in 330 s of attached
- H plasma in standard configuration
- single injection location in one half module

- EMC3-EIRENE plasma background which matches plasma conditions and heat flux
- WallDYN-3D material transport modelling and surface composition
- assume <sup>13</sup>C atomic source injection

- local deposition near to injection location in island at same half module (1 and 2)
- global deposition on vertical target (3)
- small, but toroidally smeared deposition near strike-line location (multiple cycles)



Good agreement between NRA and WallDYN-3D

## Conclusion for Long-Pulse Operation in W7-X

- plasma operation with the uncooled graphite test divertor provided vital information on the operational window and PWI processes in W7-X
- operational window widens with the application of boronisation, reducing the impurity production by oxygen / carbon ions on graphite
- plasma operation in attached divertor conditions causes peak C erosion of more than 10 µm or rates of 2 nm/s after boronisation

- best documented plasma from PWI perspective is the standard divertor configuration used for more than 50% of the time in OP B
- net C erosion follows the heat and particle footprint on the divertor target plates with local deposition zones away from the contact point
- material migration paths studied with ERO2.0 and WallDYN-3D with predominant role of divertor in total C erosion and deposition pattern impact of the first wall on C migration under assessment (see C.P. Dhard PFMC 2021) => moderate local erosion/deposition observed

- considering only operation after boronisation and with negligible O level in the plasma (<0.1%): extrapolate to long-pulse operation
- total accumulated H plasma time in standard configuration in OP B (4809s) equivalent to almost 3 W7-X discharges of envisaged 30 min.
- total C erosion rate in the divertor is about 4.2 mg/s or 20g over the campaign which would convert to 7.6g C per 30 min. discharge
- the total C erosion as well as the peak C erosion could hamper plasma operation and cause dust issues in campaigns with long pulses

- reduction of C erosion is advisable and could be achieved by transfer to detached divertor operation (see O. Schmitz et al. 2021 NF 61)
- predictive modelling with ERO2.0 and WallDYN-3D should be carried out to simulate PSI in long pulse discharges with attached and detached divertor conditions

This work has been carried out within the framework of the EUROfusion Consortium and has received funding from the Euratom research and training programme 2014-2018 and 2019-2020 under grant agreement No 633053. The views and opinions expressed herein do not necessarily reflect those of the European Commission.