



**FUSION
FOR
ENERGY**

Summary EX (part 2)

Gabriella Saibene
(Fusion for Energy)

Dedicated to Mario Gagliardi (15.09.1982 – 01.05.2021),
dear colleague, friend and brilliant fusion engineer

DISCLAIMERS


I apologize in advance for including just a fraction of the contributions presented at the Conference, in the Experimental area (full inclusion is Mission Impossible)

I also apologize for any error in interpretation of your results: in case, please contact me after the conference and I will rectify them for the Nuclear Fusion paper (gabriella.Saibene@f4e.Europa.eu)

DG Bigot [OV 1-1] identified the validation of ITER Research Plan as central for its effective execution

IRP → required R&D entrusted to the plasma fusion communities, in particular

1. Divertor (and wall) load controls → ELM suppression
2. Effective disruption detection and **mitigation**
3. Development of plasma scenarios with required performance (Q and Pfus), compatible with ITER constraints (actuators PFC lifetime, ...).



The results presented at this conference show remarkable progress in all major priority areas for ITER (and beyond).


This conference has also highlighted the importance of experiment design driven by modelling (predict first)

Two main takes:

1. Scenarios supporting the development of integrated performance as required in ITER have been established in many machines, and using different approaches and actuators
2. At the same time, new ideas emerge opening active lines of research (disruption mitigation one of those)

ELM suppression by $n = 4$ RMP in EAST Demonstrated in EAST for first time and in low input torque plasmas

A Loarte Y Sun
EX4/4



□ Conditions similar to high Q
ITER H-modes

➤ **low torque** $T_{NBI} \rightarrow 0.44 \text{ N}\cdot\text{m}$ ($< 0.9 \text{ N}\cdot\text{m}$ ITER 33 MW-NBI equivalent)

➤ $q_{95} \sim 3.65$, $v_{*e,ped} \sim 0.5$, $\beta_N \sim 1.5$

➤ $T_i \sim T_e \sim 1.5\text{-}2 \text{ keV}$

□ No drop in energy confinement

➤ Small density pump out

➤ Low W concentration during RMP application





Optimum ITER high Q scenario integration of ELM Suppression with $n = 4$ RMP in EAST

A Loarte Y Sun EX4/4

High energy and particle confinement maintained


Good control of divertor power fluxes (separatrix + **off-separatrix**)



Optimized coupling with RMP fields leads to ELM suppression

S W Yoon OV 2-3

Evidence of up/down asymmetric coupling difference for RMP ELM suppression, showing a meritorious use of Mid/Bot, instead of Top/Mid




- Potentially critical information for ITER RMP operation
- Much more reduced level of Bottom row was found to be sufficient, suggesting a weak coupling of top-row in 3-row IMCs

Stationary Scenarios for the DT phase achieved: baseline route -



Baseline: 3 MA/2.8 T ($q_{95}=3.1$)



- $H_{98}(y,2) = 1.05$, $\beta_N = 2.2$, $\beta_p = 0.9$, $f_{GLD} \sim 0.7$
- Improvement wrt Type-I ELMs plasmas
 - Reduced gas puff + Pellets (45Hz):
high confinement
 - Inclusion of **small Ne quantities**
provides stability [C. Giroud IFE/P4-12]
- **Long phases with high frequency (200-400Hz) small ELMs**
- Core radiated power stable
- Divertor in 'attached' conditions


J Garcia EX 1-2 and E de la Luna EX 3-2

Differences between small and Type-I ELMs plasmas at same input power – J Garcia EX 1-2



Type-I ELM: only gas

Small ELM: gas+pellets+Ne




- Compared to type-I ELMs, small ELMs pulses are characterized by:
 - Higher density peaking
 - Wider pedestal at the same pedestal top pressure
 - $T_i/T_e > 1$ including the pedestal top
 - Higher rotation and rotation shear (close to ITER predictions) [C. Chrystal NF 2020]
 - Higher DD neutron rate




Wider density pedestal and high T_i^{PED} correlated with the onset of small ELMs



#94777 (gas fuelled, Type I ELMs)



#94442 (no-gas, small ELMs)




- Compared to the ELMy H-mode plasma, the discharge with small ELMs has:
 - similar P^{PED} (lower n_e^{PED} , but higher T_e^{PED} , T_i^{PED})
 - wider n_e and P_e pedestal width, significantly lower maximum ∇n_e & ∇p_e .
 - position of maximum gradient shifted inwards (due to wider width) → improved pedestal stability

E de la Luna, EX 3-2

Extensive studies of "natural" small ELM regimes in Asdex-U, including I-modes, EDAs and QCE. U Stroth [OV2-2]

QCE: high-power discharge without any large ELM



An integrated scenario at DEMO relevant separatrix parameters


- High power (15 MW), partially detached divertor, close to H-mode confinement
- Quasi continuous transport by small (type II) ELMs
- Power fall-off length 4 times larger than between ELMs in H-Mode

→ poster by M. Faitsch et al.

[M. Faitsch et al. NME 2020]



Integrated no-ELM scenario in AUG: EDA H-mode extended to high power by controlled Ar seeding



power to divertor controlled via Ar seeding

quite narrow power window in Psep for L-EDA-ELMy

very good performance: $H_{98} > 1$,
 $n/n_{GW} = 0.9$, $\beta_N = 2$,
 integration with detachment shown with Ar+N

low tungsten concentration $< 10^{-5}$

completely ELM-free

QCM @ 20-30 kHz provides full ELM suppression
 via MHD-stable pedestal

A Kallenbach EX 2-5

EDA H \rightarrow L-mode due to radiation event



WEST experiments demonstrate very long plasmas with W divertor [Bucalossi OV 2-1]

Long pulse discharges with duration 30 s – 1 min routinely performed in Phase I

- ▶ 9 MW of combined ICRF/LHCD power coupled, without W accumulation
- ▶ Wall monitoring system for RT metallic PFC protection implemented
- ▶ No failure on ITER-grade PFU prototypes (from CN, EU and JPN) but evidence of damages after several hours of plasma at moderate heat fluxes:
 - ✓ Optical hot spot observed for the first time as predicted by modeling
 - ✓ Cracks and local melting observed at moderate heat flux on misaligned PFUs from 0.3mm - 0.8mm → **crucial issues for safe operation in ITER and divertor lifetime**

Phase II with the full ITER-grade divertor aiming at 1000s plasmas to start in summer 2021


- ▶ 456 PFUs manufactured and reception tests completed → assembly ongoing
- ▶ Main thrusts for phase 2:
 - ✓ Combined high heat flux/high particle fluences studies
 - ✓ Towards **steady-state H-mode operation in full W device**



Improved actuators (off-axis NB) for profile & q control in DIII-D



M Fenstermacher [OV 1-3]

Performance of High- q_{\min} Plasmas Improved by Increased Off-Axis NB Power Reducing AE Drive and Fast Ion Losses



- Reduced beam pressure gradient at $\rho_{q_{\min}}$ gives higher thermal pressure and ratio of neutrons/TRANSP(classical)

- New off-axis NBI current drive matches simulations





- Recovered up to 25% of neutrons ratio (35% with added ECCD)
- 10% higher confinement, 15% higher β_N

Optimization to classical fast ion confinement possible in steady state reactor scenarios

Multi-pass EC 2nd harmonic O-mode key for sustained high n plasmas

High density operation

O2 ECRH operation with 6 MW sustained a density of $1.4 \cdot 10^{20} \text{ m}^{-3}$, where strong electron ion coupling could be achieved.





H O Laqua, P6 6

EC HFS vertical injection in DIII-D reaches predicted high CD efficiency

Xi Chen [EX 1-1]

Doubling of Off-axis ECCD Achieved on DIII-D via Reactor-relevant 'Top Launch ECCD' Approach

- New top launch ECCD system is installed on DIII-D to allow experimental validation
- Experiments tested main tenets of top launch ECCD
 - Geometry allows selective wave interaction with high $V_{||}$ electrons having high CD efficiency
 - Long absorption path compensates for inherently weak damping at high $V_{||}$



H + He₃ ICRH heating in JET 3rd harmonic D in AUG




Figure 4 Neutron rate as a function of ICRF+NBI power in discharges with different ICRF schemes

JET – Hybrid scenarios with combined NB and ICRH heating





Figure 8 Plasma parameters for AUG discharge 35489 with 3rd harmonic ICRF heating of D with synergy with D NBI. Different NBI injectors were used for each ICRF phase.

Pure e-heating steady state H-mode with W divertor achieved in EAST

— B N Wan [OV 1-4]

EAST demonstrated high β_p long pulse H-mode operation with high f_{bs}




- A 60s steady-state high β_p H-mode discharge achieved by optimizing core and edge compatible integration.

- $\beta_p \sim 2.1$, $f_{bs} \sim 0.5$, $H_{98} > 1.3$, small ELMs
- eITB ($T_e > T_i$), zero torque, low rotation

- Fully non-inductive high β_p regimes close to 1GW CFETR performance obtained by Improving confinement

- Higher β_p
- Higher density gradient
- Reduced fast ion losses





Development and Experimental Qualification of Novel Disruption Prevention Techniques on DIII-D

J Barr EX-5

Also F Felici EX-P4-21

- **DIII-D Disruption Free Protocol:**
 - Initiative for qualifying comprehensive disruption prevention tools in DIII-D
- **Novel real-time proximity-to-Instability controller for avoidance of stability limits**
 - Applied for robust VDE prevention
- **Novel soft-landing technique generates warm, helical core after thermal quench**
 - Significantly slow current quench
- **Rigorously qualifying emergency shutdown for disruption avoidance**
 - Transitioning to limited for emergency shutdown significantly improves chances of success



J. Barr/ITER FEC 2020/May 14th, 2021




Disruption mitigation – thermal energy dissipation

D Shiraki EX-5-2 Ra

TQ radiation asymmetry due to localized injection source is observed experimentally and in extended-MHD simulations

Collaboration DIII-D,
Eurofusion, JET and
Oak Ridge Nat Lab

- **Asymmetries observed from comparing first-wall IR thermography for different SPI systems**
- **Radiation peak is broadly centered around SPI port**
 - Due to rapid localized injection, rather than MHD heat flux
- **Estimated TQ toroidal peaking factor**
= $1.9 \pm 0.5/-0.3$
 - Consistent with DIII-D NIMROD simulations¹
- **Close to ITER surface melt limit² (peaking factor ~ 2)**
 - Not yet known if multiple SPIs reduce peaking



9



¹ C. Kim, et al., This conference


² M. Sugihara, et al., Nucl. Fusion **47** (2007) 337

D. Shiraki/IAEA-FEC/May 14, 2021

S Jachmich
EX-5-1 Ra

Radiation efficiency


- Vary P_{NBI} to scan f_{th} ($W_{\text{th}}=0.3\text{-}1.5\text{MJ}$ for $W_{\text{mag}}\sim 3\text{ MJ}$)
 - Pellet: 80% Ne ($\text{Ne}=2.4\times 10^{22}$ atoms + D-shell)
- Axisymmetric weighted is significant lower than 100%



➤ Difference in W_{rad} measured by 2 bolometers
→ radiation asymmetries

Radiated energy fraction: $\langle f_{\text{rad}} \rangle = W_{\text{rad},H} / (W_{\text{mag}} + W_{\text{th}} - W_{\text{coupled}})$
Thermal energy fraction: $f_{\text{th}} = W_{\text{th}} / (W_{\text{mag}} + W_{\text{th}} - W_{\text{coupled}})$

- Fast cameras show large helical structure: SPI-location



- Emis3D code to determine helical structure fitting best the LOSs of the bolometers
- Assumes Gaussian toroidal distribution using $P_{\text{rad},V}$ and $P_{\text{rad},H}$ as boundaries

➤ Toroidal peaking ~ 2.2

R. Sweeney et al, 62nd APS DPP meeting, 2020

Paz Soldan
EX-5-2 Rb

DIII-D and JET

New Approach to Runaway Electron Mitigation Demonstrates Safe Termination of MA-Level RE Beams

Approach involves

1. Deuterium Injection
2. Excite Current-Driven MHD (big $\delta B/B$)
3. "Disruption of RE beam" \rightarrow sub-ms loss

Safe RE Termination Achieved By:

- Low-Z: recombines background plasma \rightarrow accelerates Alfvénic MHD
- Large $\delta B/B$: REs lost to wall over large wetted area \rightarrow disperse kinetic energy
- Current converts back into Ohmic bulk \rightarrow Magnetic energy dissipates benignly



New Approach Avoids First Wall Heating Despite High RE Energy



EUROfusion

EX/5-2b

C Paz-Soldan/IAEA-FEC/2021-05



C. Reux et al, Phys. Rev. Lett 2021

C. Paz-Soldan et al, Plas. Phys. Contrl. Fus 2019

Extended MHD Modeling Reproduces RE → Ohmic Current Transfer in DIII-D and JET


Paz Soldan
EX-5-2 Rb

- M3D-C1 and JOREK with RE fluid model deployed
- Near-total stochasticity found in both simulations
- Prompt loss of REs drives current transfer to the bulk
- Dissipation of magnetic energy into line radiation
 - ... Not back into RE energy


Ideal Scenario for
Magnetic Energy Handling



Early Growth Stochasticity



DIII-D (M3D-C1)



JET (JOREK)

C. Liu et al, Phys. Plasmas (in preparation, 2021)
V. Bandaru et al, Plas. Phys. Contr. Fus. 2021



B_T Compatible – intershot cleaning with ECWC in KSTAR - S W Yoon OV 2-3



21

Electron cyclotron wall cleaning can be a good solution for wall recovery from massive material injection.

KSTAR shots: ['022856', '022858', '022860', '022861', '022863', '022865', '022866']



ECWC

Ne:D=0.05:0.95 (all 7 mm SPI pellets except 4.5 mm pellet of #22856)

X2 harmonic EC-assisted start-up at $B_T=1.8$ T + X2 harmonic ECWC

- #22856 (SPI) → #22857 (ECWC) → #22858 (SPI) → #22869 (ECWC) → #22860 (NBI fault) → #22861 (SPI) → #22862 (ECWC) → #22863 (SPI) → #22864 (ECWC) → #22865 (NBI fault) → #22866 (SPI)

The scientific and technical content of the material presented in this conference is remarkable, with quality and coherence of the fusion community work increasing consistently.

ITER is becoming a reality (not only buildings, with all my respect to buildings) and this helps towards channeling ideas and resources to sustain the ITER Research Plan .

Performance & reproducibility of ELM control and suppression, pedestal control, disruption mitigation, additional heating, .. is impressive . Modeling is now guiding experiments, not only interpreting results.

The holy grail of the integrated scenarios, as necessary for ITER success, seems to me much nearer than ever before.