



Fast Reactor Program in India



Dr. B.Venkatraman
Distinguished Scientist and Director,
Indira Gandhi Centre for Atomic Research
Chairman and Managing Director (In Charge),
Bharatiya Nabhikiya Vidyut Nigam (BHAVINI) Limited
Senior Professor, Homi Bhabha National Institute
Kalpakkam

Plenary Talk
International Conference on Fast Reactors and Related Fuel Cycles:
Sustainable Clean Energy for the Future (FR22)
19–22 April 2022, Vienna, Austria




Structure of the Talk



- **Role and advantages of Fast Reactors – Indian Context**
- **Fast Breeder Test Reactor**
 - Genesis
 - Status
 - Lessons learnt over the last 36 years
 - Role in fast reactor fuel, structural material and human resource development
 - Life Extension Program
- **Post Irradiation Examination of Fuels – Challenges and Significant Results**
- **Reprocessing of Fuels – Challenges**
- **Indian Fast Reactor Program – Way forward**

Fast Reactors : Catalytic Linkage



- ✓ Provides perfect link covering natural nuclear resources of India
- ✓ Effective and optimal utilization of uranium
 - Better resource management
- ✓ Long term energy supply
- ✓ Higher growth rate with breeding
- ✓ Waste management
 - Incineration of radioactive waste from spent fuel
 - Reduction in long-term storage requirements
- ✓ Enhanced performance parameters
 - High temperature of operation
 - Higher thermodynamic efficiency
- ✓ Closed fuel cycle program is essential

Indira Gandhi Centre for Atomic Research Kalpakkam

Kalpakkam : Unique complex internationally with reactor systems utilizing all the three fissile isotopes – U235, Pu-239 and U-233



Fast Breeder Test Reactor:
Pu-239 (Operation)



Madras Atomic Power Station:
U-235 (Operation)



Prototype Fast Breeder Reactor:
Pu-239 (Comissioning)



KAMINI:
U-233 (Operation)



Fast Breeder Test Reactor (FBTR) – Genesis/Status



- ★ 1968 - Decision to initiate fast reactor programme, beginning of FBTR in Fast Reactor Section of Reactor Engineering Division, BARC.
- ★ 1969-Agreement signed between CEA and DAE to prepare project report to set up a fast breeder test reactor
- ★ 1971 - Dedicated Centre setup at Kalpakkam -Reactor Research Centre – renamed Indira Gandhi Centre for Atomic Research (1985).
- ★ 1972 - Ground breaking for the Fast Breeder Test Reactor. Parallely other facilities initiated.
- ★ ~1978 – Decision to use Carbide Fuel
- ★ Oct. 18, 1985 – First Criticality
- ★ July 2006 - MK-I fuel reaches burnup of 155 GWD/t without failure
- ★ Dec. 2009 – PFBR test fuel achieves target BU of 112 GWD/t at LHR of 450 W/cm
- ★ **March 07, 2022 FBTR attains rated capacity - 40 MWt / 10 MWe**

Unique U-Pu mixed
carbide fuel. Record burn-
up of 165 GWd/t –
international milestone.

36 years of successful
operation without any
major incidence

Indigenously developed sodium
pumps login > 8,70,000 trouble-
free cumulative service.


Operated at power level of
40 MWt;

Electrical Power generated
10.0MWe



Cradle for Human
Resource Development in
Fast Reactors

Irradiation of yttria yielded ^{89}Sr ,
for the first time in India, used as
a palliative for cancer patients –
Societal Application



30th Irradiation Campaign 68 SA Core


FBTR: Cradle of Human Resources

Grade	Number of personnel Trained
Engineers	57 (FBTR) 38 (BHAVINI) 6 Licences for FBTR operation
Scientific Assistants	29
Technicians	55




O&M Personnel of PFBR undergoing training in FBTR

Irradiation of various fuels



Irradiation of various structural materials



- FBTR has completed 36 years of safe & successful operation.
- Various studies carried out for extending the life of FBTR.
- The operational life of FBTR limited by the neutron damage to the grid plate which is a non-replaceable component.
- Limiting residual ductility of 10% uniform elongation is attained at 6.3 dpa for FBTR grid plate.
- At the end of 29th irradiation campaign, grid plate has accumulated 2.35 dpa
- Remaining residual life corresponding to 6.3 dpa: ~ 8 EFPY
- WC pellets planned to be introduced as lower axial shield in FSAs to reduce the fluence on the grid plate.
- By this, Life of FBTR extends by ~ 33% i.e. to limiting dpa - 8.19.
- FBTR expected to operate upto 2034/2035.

Challenges faced successfully during operation of FBTR

- In the last 36 years of operation, FBTR has faced several challenges. This includes
 - Fuel handling incident
 - Sodium leak from bellows sealed sodium service valves
 - Choking of hot argon communication lines between primary capacities
 - Leak from embedded biological shield concrete cooling coils
 - Fuel clad failure
 - Steam generator tube leak and its replacement



Challenges in PIE of FR Materials

Characteristics of FR Core

- High power density
- Compact core
- Efficient coolant is essential (sodium)
- High burn-up
- High fluence

Reactor →	Thermal	Fast Breeder
Fissile enrichment	0 – 3 % ²³⁵ U	10 – 30 % ²³⁹ Pu
Ave. neutron energy	0.025 eV	100 keV
Burn-up (GWd/t)	~ 30	~ 100
neutron flux n/cm ² .s	10 ¹⁴	5 – 10 × 10 ¹⁵
neutron fluence	10 ²²	2 – 10 × 10 ²³
Ave. core power density, W/cm ³	~ 100	~ 300 - 400

Main factors that influence burn-up:
sodium inlet temperature and LHR

Clement, 2020

Parameters for stage-wise increase of LHR and burn-up

- **Post-irradiation Examination**
 - Fuel swelling rate | Internal porosity within fuel | Fission gas release | Cladding and wrapper swelling and creep | Cladding - Pellet gap | Clad strain | Wrapper dilation | Fuel bundle wrapper mechanical interaction
- **Reactor Operations**
 - SA extraction force
- **Thermomechanical modelling**
 - Flow reduction through SA | Cumulative damage fraction on clad

Criteria for burn-up limit


- ◆ FG induced creep rupture
- ◆ Creep rupture due to FCMI
- ◆ Porosity exhaustion
- ◆ Hex-can sheath deformation
- ◆ Pin – duct interaction
- ◆ Residual ductility of cladding and duct

High burn-up FR fuels and other materials involve handling of $\alpha\beta\gamma$ – high active fuel and potentially α -active structural materials, requiring specialised hot-cells, shielding and handling


PIE of irradiated FR Fuels – burn-up limits

Carbide Fuel 25-155 GWd/t



- Fuel pin cross-sections of 25 and 50 GWd/t burn-up fuel pins indicate radial cracks and progressive reduction in the fuel-clad gap
 - free fuel swelling rate estimated ~1 to 1.2% per atom% burn-up
 - lower than expected value (fuel design)
- At 100 and 155 GWd/t burn-up, fuel-clad gap is closed along the entire length of the fuel column
 - circumferential cracks indicate restrained swelling
 - porosity free outer rim at 155 GWd/t fuel pin cross-section due to creep of the fuel due under FCMI stress



MOX Fuel 112 GWd/t




Fuel-Clad gap reduction from 90-110 μm to 13 μm in 13 EFPD – BoL low LHR duration for fresh fuel



Venkiteswaran *et al.*, 10.1016/j.jnucmat.2014.01.045 (2014), Jayaraj *et al.*, 10.1016/j.jnucmat.2018.06.001 (2018)


Comprehensive PIE of PFBR MOX fuel and Dg clad/wrapper indicated safe operation to rated burn-up of 100 GWd/t. FCMI and clad wastage due to FCCI could be life limiting precursors at higher burn-ups.

Fuel cladding behaviour SS316 and Alloy D9



Swelling of SS316 and Alloy D9 wrappers of FBTR at various dpa corresponding to fuel burn-up up to 155 GWd/t (SS316, carbide fuel) and 112 GWd/t (Alloy D9, MOX fuel).

Reddy *et al.*, DOI 10.1520/MPC20200208 (2022)



AISI 316 and D9 claddings irradiated in FBTR: UTS reduction at locations of high swelling

Karthik *et al.*,(2022)

10.1016/j.jnucmat.2022.153711

CHALLENGES

Thermal Vs Fast Reactor Fuel Reprocessing

Thermal Reactor fuel

Low burnup (6700 MWd/ton)
Long cooled (> 5 yrs)
Low specific activity (~300 Ci/kg)
Low Pu content (0.3%)

Contact maintenance
-> Cell entry feasible

Dynamic containment is generally
adequate

Fast Reactor fuel

Very high burnup (1,00,000 MWd/ton)

Short cooled (<1yr)

High specific activity (~10,000 Ci/kg)

High Pu content (>20%)

70% for **FBTR carbide fuel**,

44% for **FBTR oxide fuel**,

21% (inner core) and

28% (outer core) for **PFBR fuel**

Remote maintenance

->Cell entry generally **not** feasible

Static containment is required (Leak tight
cells required for handling high Pu content)

Status of COmpact facility for Reprocessing of Advanced fuels in Lead cells - CORAL

Closing the fuel cycle for FBTR

- Operational since 2003
- Objectives met
 - Development and optimisation of process for Fast reactor fuel reprocessing
 - Validation of several first-of-its-kind equipment for process, remote handling
 - Establishing analytical techniques
- Reprocessed Pu was refabricated into fuel and it is generating power in FBTR. Closure of FBR fuel cycle has been demonstrated.
- Successfully completed processing of 61 campaigns of FBTR fuel with maximum burn-up of 155 GWD/ton and continues to operate



CORAL operating area



Inside cell view of CORAL

INDIAN FAST REACTOR FUEL REPROCESSING PROGRAM

Phase I



CORAL
Pilot facility

DFRP
Demo facility

FRP@FRFCF
(Prototype facility)

Phase II



Technical know how

Stage-I

- Process and equipment development

Phase III



Stage-II

- Pilot Plant (CORAL)

Phase IV



Stage-III

- Demonstration plant (DFRP)

Stage-IV

- Commercial scale plants (Starting with FRFCF)



Phase III

Sodium bonded Metal Fuel Pin Fabrication Facility

- A metal fuel fabrication Laboratory has been set-up with high purity inert atmosphere glove box train.
-
- Flow sheet and process equipment development including injection casting technology & fuel pin welding (T91) established.
- Sodium bonded metal fuel pins of U-6Zr, EU-6Zr, U-19Pu-6Zr, EU-23Pu-6Zr fuel pins fabricated and are currently under irradiation at FBTR.



Sodium boned metal fuel pin fabrication facility

- Slugs qualification (physical & chemical)
- Slug loading & settling
- End-plug welding & Post Weld Heat Treatment (PWHT)
- Sodium Bonding
- HLT and Pin qualification

Pyrochemical Reprocessing

- Development of pyrochemical technique based on molten salt electrorefining is planned for reprocessing of spent fuel from metal fuel fast reactors.
- Electro-refining of Uranium (U) and U alloys small scale demonstrated.
- Electro-refining of irradiated U-Zr and U-Pu-Zr at small scale demonstrated at Hotcells.
- An engineering scale facility – few kg scale Pyro Process R&D Facility is set-up for scaled up pyroprocessing studies. Alloys of natural U containing surrogates for Pu and typical fission products will be used for electro-refining. Electro-refining of Uranium at small kg scale is under progress.



Way forward...

- **Setting up of facility for fabrication & quality control of sodium bonded metal fuel pins and fabrication of qualified 1.0 m length fuel pin subassembly (37 fuel Pin) for irradiation at FBTR.**
- **Fabrication of subsequent test fuel pins of varying composition / enrichment to achieve target LHR.**
- **Establishing pyroprocessing facility for spent fuel of sub-assembly level & flow sheet for re-fabrication to close fuel cycle.**

2030

A detailed cross-sectional diagram of a nuclear reactor core. The diagram shows a central vertical assembly with a fuel element (08) in the center, surrounded by a moderator/reflector (06). The core is housed within a pressure vessel (01) with a top head (02) and a bottom head (03). The vessel is supported by a base (04). The core is surrounded by a moderator/reflector (06) and a pressure boundary (07). The vessel is filled with a fluid (09) and has a top head (10) and a bottom head (11). The vessel is surrounded by a moderator/reflector (12).

2047

Metallic Fuel Fast Reactor Program-Way forward




Engineering Scale demonstration of
(a) sodium bonded metal fuel pin fabrication
(b) Pyrochemical processing
Pilot scale plants for both colocated at Kalpakkam

**FBTR – 2 : Metallic fuel
 based reactor 100 /320
 MWth at Kalpakkam**

FBTR-Metal

- 500/1000 MWe
- Pool Type
- Metallic fuel
- Serial constr.
- Indigenous



**FBTR -2 by 2040
 and
 subsequently
 after 2050 metal
 fuel based
 reactors**

*Thanks to Organising Committee – FR 22,
IAEA, DAE*

Thank You

