


# Control and protection challenges in fully metallic tokamak WEST for long pulse operation



P. Moreau, R. Nouilletas, R. Mitteau, S. Kerboua Benlarbi, C. Reux, A. Gallo,  
P. Maget, T. Loarer, B. Santraine, J. Colnel, J. Gaspar and the WEST team



- WEST is a mid-size superconducting tokamak operated in a fully metallic environment (W)



$I_p$ ( $q_{95} \sim 2.5$ )	1.0 MA
$B_\phi$	3.7 T
$R / a$	2.5 / 0.5 m
$V_p$	15 m <sup>3</sup>
$P_{add}$	16 MW (9+7) (+3 ECRH >= 2024)
$T_{flattop}$	1000 s



► WEST key missions are twofold:

- Paving the way towards the ITER actively cooled tungsten divertor procurement and operation
- Mastering integrated scenarios **over relevant plasma wall equilibrium time scale** in a metallic environment






Plasma operation on short time scale (~10 seconds) might not reach any limit.  
Situation might differ on longer time scale (minutes, hours)

- ▶ Purpose: being able to pursue the discharge
- ▶ Solution: dealing with unexpected events on RT (e.g. apply predefined strategies)

- ▶ Concepts for long pulse operation / implementation on WEST
- ▶ Scenario design in terms of operation and plasma control
- ▶ Machine protection
- ▶ Future developments

- ▶ Concepts for long pulse operation / implementation on WEST
- ▶ Scenario design in terms of operation and plasma control
- ▶ Machine protection
- ▶ Future developments

► Plasma discharge = set of consecutive phases (segments)



► Event mitigation strategies: stage approach based on 4 levels

### Event detection

#### → Plasma scenario

Plasma state transition (MHD, H/L transition, instabilities, impurities, etc.)

#### → Plant systems

Temporary unavailability?

Total/partial unavailability?

Reduced accuracy, plant operation limits, etc.

### Event identification

- Event classification
- Prioritization

### Event handling

1- Brief adjustment before coming back to ref. scenario

2- Slightly degraded plasma vs ref. (within a preset envelope)

3- Switch to plasma backup scenario (change segment)


4- Trigger a Soft / Fast plasma shutdown

Plasma controller

Segment Manager

## Main features of the Plasma Control System

- ▶ Based on DCS (Discharge Control System) developed at IPP for ASDEX-upgrade and configured for WEST
- ▶ Plasma controllers developed and validated in Matlab Simulink. Automatic C++ code generation and implementation.
- ▶ Segment oriented and event management natively implemented (**segment manager / Waveform generator**). Switch to another segment when outside plasma scenario envelop
- ▶ Specific Pulse Schedule Editor is used to prepare the plasma discharges



- ▶ The IPP W7-X Pulse Schedule Editor Xedit configured for WEST needs
  - ▶ Segment management layer is used to trigger a new segment on event detection
    - List of event and policies specified: duration, MHD, communication issue, parameter outside predefined envelop, etc.
    - E.g. specific plasma termination designed for: flux limit, runaway detection, network communication lost, etc.
    - Offer flexibility to address new events

List of events resulting in triggering a new segment


- WEST\_SegmentManagement
- Segment characteristics
  - Segment identifier
  - Transition time
  - Segment duration
  - Next segment to trigger
- Plasma phase event
- Plasma current control failed event
- Magnetic control failed event
- Fueling control failed event
- LHCD system failed event
- ICRH system failed event
- Cu High Impurity level detection event
- Fe High Impurity level detection event
- W High Impurity level detection event
- Disruption detection event
- High MHD level event
- Calorimetry protection event
- LPA protection event
- ARRPREM event
- Plasma current end event
- End of flux event
- Poloidal overheating event
- High radiated power ratio event
- Limiter to X point Transition
- X point to Limiter Transition
- L to H mode transition
- H to L mode transition
- Generic Timing System event 1
- Generic Timing System event 2

## Set of segments used to build a plasma discharge


- Goal: stay within the operation envelop while ensuring the plasma scenario / Performance

- ▶ Concepts for long pulse operation / implementation on WEST
- ▶ **Scenario design in terms of operation and plasma control**
- ▶ Machine protection
- ▶ Future developments


- ▶ WEST TF coils are superconducting,  
WEST PF and CS are made of Cu actively cooled
- ▶ Total flux swing available CS + iron core: 14 Wb  
(CS current: 40 kA  $\downarrow$  -30 kA)
- ▶ Model of flux consumption done to identify limitation
- ▶ Tiny range of current in CS for CW operation ( $\pm 3$  kA)
- ▶ Main limitation in the CS due to heat load in the coil  
**NOT** due to the flux swing available.  
~120s achievable with  $V_{loop} \sim 45$ mV or 60mV (optimized startup phase)



- ▶ Longer Duration (> 120 s): obtained for  $V_{loop} \sim 0$  V AND transition when the CS current is in the range  $\pm 3$  kA  
→ adjust plasma scenario



- Divertor coils made of Cu actively cooled
- Finite element cooling model implemented in real time




$$T_{Cu}(i) = T_{Cu}(i) - \alpha [T_{Cu}(i) - T_{H2O}(i)] \Delta t + \beta I_{div}^2$$

$$T_{H2O}(i) = (1 - \gamma) T_{H2O}(i) + \gamma T_{H2O}(i - 1) + f(T_{Cu} - T_{H2O}) \Delta t$$


$$T_{H2O}(0) = T_{input} = 50 \text{ or } 70^\circ\text{C} \quad \textcolor{red}{T_{output} < 100^\circ\text{C}}$$

- Max CW current in the divertor coils 12.5 kA
- No continuous operation for  $I_p > 700$  kA



► Implemented control

- $I_p$  controlled through LHCD power
- $V_{loop}$  controlled through  $V_{CS}$



► Controller not yet validated on plasma but tested on simulation  $V_{loop}$

- Magnetic controller same as on the tokamak
- Heating controller same as on the tokamak
- FEEQS + 0D model of flux consumption (parameters tuned to fit with the pulse data)


► Example based on shot 56727:  $I_p = 480\text{kA}$

Switch ON controller at 3 s:  $V_{loop} = 0.1\text{V}$

Saturated LHCD power to a prescribed value





$\sim 2 \times 2.8 \text{ MW}$  needed to sustain  $I_p = 480\text{kA}$  with  $V_{loop} = 0.1\text{V}$

Control CS voltage to obtain  $V_{loop} = 0.1\text{V}$




- ▶ Concepts for long pulse operation / implementation on WEST
- ▶ Scenario design in terms of operation and plasma control
- ▶ **Machine protection**
- ▶ Future developments

- IR: Extensive coverage of the in-vessel components




- Principle of the protection: interlock and limit avoidance



## WEST capabilities


11 IR cameras ( $3.9 \mu\text{m}$ ,  $\delta\lambda=200 \text{ nm}$ ) on WEST  
99% of availability. Additional power limited to 1MW – 1s without the IR diagnostic  
35 Regions of interest monitored 12 on real time  
 $T_2 - T_1 = 50^\circ\text{C}$ ;  $T_{\text{interlock}} = T_2$

- ▶ Image interpretation based on scene modeling including reflections





- Prediction of deposited & reflected fluxes from the magnetic equilibrium

- ▶ Evaluate real temperature from apparent temperature and emissivity






- Large variations of the divertor emissivity
- Emissivity  $\sim 0.15$  and remains constant at the ISP and OSP positions (similar to pre-exposition values)

- Overheating of ripple protection. Results in LHCD power decrease. No effect on ICRH



- ▶ High content of metallic impurities Cu, Ag and/or Fe might be a sign of an on-going damage of an in-vessel component
- ▶ Copper is only present on the LHCD launcher: if Cu content > prescribed value then LHCD power is reduced until proper level is recovered
- ▶ if Fe content > prescribed value then LHCD AND ICRH powers are reduced until proper level is recovered
- ▶ When the event is mitigated, the power comes back to the nominal value







- Heat flux density on divertor  
**(Max 10 MW/m<sup>2</sup>)**
- Total thermal load  
**(Max 10 MW)**
- Energy deposited on unsupervised area  
**(Max VV below 2.2MJ/m<sup>2</sup>)**

$$q_{deposited}^{osp} = r^{out} \times r^{ripple} \times \frac{P_{cond}}{2\pi R^{osp} \lambda_q^{omp} \frac{B_{poloidal}^{omp}}{B_{total}^{omp}}} \times \frac{\|\vec{B}_{total}^{osp} \wedge \vec{n}_{divertor}^{osp}\|}{\|\vec{B}_{total}^{osp}\|}$$

Annotations on the equation:

- Fixed 2/3 (blue arrow pointing to  $r^{out}$ )
- Fixed 2 (blue arrow pointing to  $r^{ripple}$ )
- Fixed 6.5mm (blue arrow pointing to  $P_{cond}$ )



### ► Allow:

- processing heat loads on supervised and unsupervised areas
- Ensure machine protection wrt thermal loads
- Control flux density on divertor for qualification under well controlled and reproducible conditions

- ▶ Concepts for long pulse operation / implementation on WEST
- ▶ Scenario design in terms of operation and plasma control
- ▶ Machine protection
- ▶ **Future developments**

► New field in fusion. Allows working on complex use-cases where data or models tend to be limited. Machine learning could enable applications from fast plasma simulations to non-linear feedback control.




► Several ongoing applications are studied at the IRFM:

- Fast detection of hot spots through infrared video signals, UFOs, etc.
- Magnetic control based on [1]

► Two paradigms are at the core of those methods:

- Supervised learning uses datasets **to identify and generalize underlying phenomena in the data**
- Reinforcement learning uses interactions with an environment through actions. **By trial and error, a « reward » signal is used by the agent to learn a given task**

On one hand, datasets are built on real shots, and on the other hand data are observed online within a simulation. Neural networks are used in both contexts.



[1] « Magnetic control of tokamak plasmas through deep reinforcement learning » - Degrave, J., Felici, F., Buchli, J. et al. - 2022

- ▶ Architecture of the WEST PCS and of the pulse schedule editor are designed to deal with events (segment approach of the discharge, event handling policies) and easily scalable
- ▶ Basic and more advanced plasma controls have been implemented:
  - Magnetic Control of plasma current: only  $I_p$  or  $(I_p, V_{loop})^*$
  - Magnetic Control of plasma position done on:  $(R, Z)_{\text{centroid}}$  or  $(EROG, Z, dX)$  or  $(EROG, Z, dSep)^*$
  - Fueling Control done on: VV pressure or plasma density (gas, SMBI and Pellets)
  - H&CD Control either feedforward or feedback (e.g.  $V_{loop}$  control)
- ▶ Machine protection also implemented in the aim of pursuing safely the discharge
  - IR protection based on measurement and reflection models
  - VUV spectroscopy measurements on Copper and Iron
  - Basic heat load modelled implemented on real time (allow the protection of unsupervised areas)
  - And also Runaway electron, interlock on subsystems or IR measurements
- ▶ Future activities
  - Implement/test control based on AI for the plasma shape, the path toward a prescribed plasma state (e.g.  $V_{loop}=0$ )
  - Improve the actuator management with equivalence rules between them (H&CD systems, valves, etc.)
  - Availability of ECRH in 2024 will allow more flexibility and will require control developments e.g. to mitigate MHD, W core contamination, etc.
  - **Ultimate target of WEST (cf. Project Plan) is to obtain long pulse discharge with 10 GJ of injected/extracted energy**

\* Still to be tested on plasma although validated on simulation



# Thank you for your attention

