

Bulk, surfaces, and grain boundaries in the lifetime of cascades

Thursday, 18 July 2024 11:50 (20 minutes)

Neutron irradiation is an engine in a fusion reactor that generates power, but not all that controllable. The uncontrollable nature of neutron in a magnetic field still needs to be controlled to some extent in order to safely operate the fusion power plant, and one of the potential solutions is to use a tough plasma-facing material. W as a plasma-facing material unavoidably has grains, and the durability of W under neutron irradiation is affected by microstructural properties such as grain size distribution.

In this talk, we compare and contrast the differences in defect population, evolution, and annihilation in the damage cascades in various environments, i.e. periodic bulk, near surface, or near grain boundaries, from atomistic calculations. In particular, we try to identify the origin of the kinetic characteristics in each environment, and how we can further improve the damage predictions from atomistic calculations to make them compatible and quantitatively consistent with experimental measurements.

This work was supported by the National Research Foundation of Korea (NRF) grant funded by the Korea government (MSIT) (No. 2020R1A2C201510913), and Korea Hydro & Nuclear Power Co., LTD (No. 2022-Tech-11).

Primary authors: Mr SHIN, Youngguk (Kyung Hee University); Ms MOUL, Vichhika (Kyung Hee University); KANG, Keonwook (Yonsei University); LEE, Byeongchan (Kyung Hee University)

Presenter: LEE, Byeongchan (Kyung Hee University)

Session Classification: PSI and PMI modelling