

ICRH SYSTEM FOR THE HL-3 TOKAMAK

Ling-Feng Lu¹, Jun Liang¹, Ya-Li Chen¹, Cheng-Gong-Hang Zhou¹, Chu-Rui Zhang¹, Zhi Li¹, Yue-Xin

Ma¹, Xing-Yu Bai¹, Bo Lu¹

¹Southwestern Institute of Physics; ² ITER organization

lulingfeng@swip.ac.cn

ABSTRACT



- 6 MW ion cyclotron range of frequencies (ICRF) power is under construction at SouthWestern Institute of Physics (SWIP), available in HL-3 at Sep. 2026.
- Radio Frequency (RF) range 25–50MHz with pulses up to 5s.
- Main ion heating schemes in D plasma: H minority & 2nd D, $f=33\text{MHz}$ at $B_0=2.2\text{T}$; In D-T plasma: He-3 minority + 2nd T with $f=25\text{MHz}$ at $B_0=2.5\text{T}$.
- RF generator consists of 4x1.5MW transmitters.
- The transmission line: 520m long, incorporates 3dB hybrid couplers.
- Matching unit: $1/4\lambda$ stub tuner, $1/2\lambda$ phase shifter + pre-matching stub.
- Two 2-strap antennas with parallel wavenumber $k_{//} \sim 6.5\text{ m}^{-1}$.

Milestones of the HL-3 tokamak



Auxiliary heating power in HL-3		
NBI	19.5MW now	41MW in 09/2026
	12MW, 2 beams,	20MW, 3 beams
ECRH	5MW+7MW	6MW+7MW+7MW
	5MW 105GHz+0.5MW	4MW 140(175) GHz+2MW
LHCD	68GHz	140G+5MW 105GHz
	2MW 3.7GHz	4MW 3.7GHz
ICRH	0	6MW, 25-50MHz

ICRH heating schemes in HL-3

- Main ion heating schemes in D plasma: H minority & 2nd D, $f=33\text{MHz}$ at 2.2T







- Main ion heating schemes in D-T plasma: 2nd T & 3He minority $f=25\text{MHz}$ at 2.5T



RF SOURCE AND TRANSMISSION LINE


- RF generator: 4x1.5MW tetrode amplifiers
- 3dB combiner & decoupler are used
- 4 transmission lines, in total 520m long. Each splits into 2 feeder lines via a T-connector.
- Matching unit composed by a phase shifter + single stub tuner + pre-matching stub
- Antenna decoupler to diminish multi-coupling
- T-connector, antenna decoupler close to voltage maximum
- Double vacuum window in each feeder line




Voltage reflection coefficient (Γ) at pre-matching stub

ANTENNA DESIGN

Electrical analysis



Three antenna configurations and their electrical circuit models





V_{max} VS normalized antenna load impedance


- Configuration C has a larger coupling resistance while maintaining a V_{max} at the feeder is selected

Mechanical constraints

- Antenna needs in vessel installation, material: FS: TZM with TiC coating, others: 316L stainless steel
- Large plasma size required by high plasma current operation and high fusion power → space constraints at the front
- Resonant Magnetic Perturbation (RMP) coils → space constraints at the back
- Available radial space for antenna: 9cm at the middle plane, 15cm at top and bottom
- Design strategy: short circuit at top and bottom, remove detour structure



Thermal analysis



- 200°C hot wall operation, antenna operates 5s with 3MW full power
- Heat load at FS: 0.6MW/m^2 , strap: 0.3MW/m^2
- The temperature at FS, antenna box and strap are 473°C, 374°C and 324°C, far less than the melting points of the 316L stainless steel (1400°C) and TZM (2623°C)
- After 15mins pulse gap, the temperature at the FS, antenna box and strap reduce to 343°C, 331°C and 238°C

CONCLUSION

- 6MW ICRH system envisaged to be complete in Sep. 2026 at SWIP
- Frequency band: 25-50MHz with main operational frequency: 33MHz for Deuterium plasma & 25MHz for Deuterium-Tritium plasma
- 4 transmission lines with total length 520m, consists of 3dB combiner and decoupler, matching unit, antenna decoupler, T connector, double vacuum window are designed
- Two 2-strap antennas, each has 4 feed lines, designed to couple 3MW. Antenna radial depth is constrained to be 9cm at middle and 15cm at poloidal ends. The frequently used detour structure has to be removed
- It is possible to operate the antenna without water cooling. However, antenna temperature must be monitored carefully

ACKNOWLEDGEMENTS / REFERENCES

- The authors would like to thank emeritus Prof. Jean-Marie Noterdaeme for many useful discussions. This work is supported by National Magnetic Confinement Fusion Science program of China under the contract number 2022YFE03090002 and the National natural Science Foundation of China under grant agreements 12375212.
- References
- [1] X. R. Duan et al, Nucl. Fusion **64**, 112021 (2024); [2] W. Zhong et al, this conference, OV /3-3 (2025); [3] L. F. Lu et al, Nucl. Fusion **63**, 066023 (2023); [4] L. Heikinheimo et al, Fus. Eng. & Des. **55**, 419 (2001); [5] L. N. Liu et al, Nucl. Fusion **64**, 066025 (2024); [6] L. F. Lu et al, Nucl. Fusion **64**, 126013 (2024); [7] V. Bobkov et al, Nucl. Mat. Energy **41**, 101742 (2024); [8] R. Diab et al, Nucl. Fusion **65**, 076038 (2025); [9] Y. Lin, J. C. Wright and S. J. Wukitch, J. Plasma Phys. **86**, 865860506 (2020); [10] Q. C. Liang et al, Nucl. Eng. Tech. **55**, 2621 (2023); [11] W. Tierens et al, Nucl. Fusion **64**, 126039 (2024);