


Accelerating Fusion Energy Industrialization through Process Standardization



IAEA

International Atomic Energy Agency

A. Iaboni¹, D. Avella², A. Buonocore², L. Cederle¹, G. Centomani¹, M. De Bastiani², D. Pettinari³, G. Ferrero³, E. Gallo¹, S. Meschini³, D. Pettinari³, F. Podenzani¹, M. Romano¹, D. Salvato², G.A. Spagnuolo¹, R. Testoni³

(1) Eni SpA, piazzale Enrico Mattei 1, 00144, Roma, Italy

(2) EniProgetti S.p.A., Via Felice Maritano 26, 20097 San Donato Milanese, Italy

(3) Department of Energy, Politecnico di Torino, Corso degli Abruzzi 24, 10129 Turin, Italy

Technical Meeting on Tritium Breeding Blankets and Associated Neutronics

02-05 set 2025, IAEA Headquarters, Vienna, Austria




Breeding Blanket (BB) and Tritium Fuel Cycle are critical topics for ensuring the availability and operability of future fusion power plants. These areas could significantly benefit from **know-how and technology transfer**, as well as from **early-stage process standardization** rooted in Eni's industrial background. The following analyses are based on a high-field tokamak reactor, consistent with the design parameters proposed by CFS for an ARC-like reactor configuration [1].

Breeding Blanket


Due to the **interplay of multiple physical phenomena** within a BB, a stepwise approach has been adopted:

- **parametric analyses** have first been carried out on **individual physical domains**,
- **integrated analyses** to capture the combined effects.


The first analyses are based on the FLiBe-based Liquid Immersion Blanket (LIB) concept [2].




Example of parametric 2D FE TH analyses on a FW module




Basecase Scenario:



First Optimization: removal of beryllium (tbc by neutronic analyses) and introduction of square channels




Further Optimization: double channel, reduction of ΔT and $T_{\min}$, reduction of welding chamfer (tbd by manufacturing)



* Legend Max capped at T limit of Inconel 718 (923 K)

Double-Bundle Heat Exchanger

FLiBe is supposed to operate both as breeding blanket and primary heat transfer fluid. The **primary heat exchangers**, with heat transfer surfaces around 10^4 m^2 , **could involve excessive tritium losses** to the environment. A Double-Bundle Heat Exchanger with integrated sweeping gas would minimize tritium permeation and allow alternative tritium recovery.



References

[1] Hillesheim (2023) APS Division of Plasma Physics Meeting 2023, abstract id.JP11.115


[2] Sorbom (2015) 10.1016/j.fusengdes.2015.07.008

Tritium Fuel Cycle


It involves the **continuous recovery, purification, and re-injection of tritium** into the plasma.

The Fuel Cycle has been **simulated with Aspen HYSYS®**, a chemical (system-based) process simulator widely adopted in the Oil & Gas sector, to assess the technical feasibility and integration of subsystems. **Add-ons have been implemented** to simulate unconventional equipment (e.g. vacuum pumps) or fluids (e.g. gas tritium or FLiBe). **The technologies with the highest TRL** have been selected.

Iterative standardized workflow



Example of workflow applied on ISS



5 The Equipment List outlines key specifications – size, duty, el. power and operating conditions – crucial for early-stage market analysis.

ITEM TAG	Q.TY	DESCRIPTION	DIMENSIONS (mm)		CAPACITY / DUTY	ELECTRIC POWER		TEMPERATURE (°C)		PRESSURE (bar)	
			ID (W)	L (H)		VALUE	UNIT	DESIGN	OPERATING	DESIGN	OPERATING
350-VA-001	1	FIRST STAGE INLET BUFFER	300	-	1000	-	-	85 / -5	25	4.5 / FV	0.8 - 2 (1)
350-KP-001A/B/C/D/E/F	6	FIRST STAGE PERMEATOR REHEATER	90 (1)	300 (1)	-	2.50	Nm ³ /h	454 / -5	25 (5) / 434 (0)	6	0.8 - 2 (1) / 4 (d)
350-HA-002	1	FIRST STAGE PERMEATOR REHEATER	200	300	150	0.16	g/h	420 / -5	743.6 (cold side) / 474.4 (hot side)	6	4 (cold side) / 1.5 (hot side)
350-HM-001	1	FIRST STAGE PERMEATOR ELECTRICAL HEATER	150	250	100	743.60	g/h	420 / -5	340 / 400	6	3.3 feed
350-XZ-001	1	FIRST STAGE PERMEATOR	100 (1)	1000 (1)	-	743.60	g/h	420 / -5	400	6 / FV	1.8 ret. side / 0.1 perm. side
350-KC-002A/B	2	FIRST STAGE SCROLL PUMP	180 (1)	253 (1)	-	2.12	Nm ³ /h	400 / -5	400	4.5 / FV	0.1 (5) / 1.3 (d)
350-KP-002A/B	2	FIRST STAGE PERMEATOR REHEATER	90 (1)	300 (1)	-	2.12	Nm ³ /h	400 / -5	35 (5) / 312 (d)	5	1 (5) / 3 (d)
350-HC-003	1	FIRST STAGE RETENTATE COOLER	250	350	200	269.2	g/h	400 / -5	400 / 25	6	1.8
350-VA-002	1	CATALYTIC STAGE INLET BUFFER	200	-	680	-	-	400 / -5	25	4.5 / FV	1.2
350-KP-003A/B	2	CATALYTIC STAGE PERMEATOR	90 (1)	300 (1)	-	0.381	Nm ³ /h	400 / -5	25 (5) / 309 (d)	6	1 (5) / 4 (d)
350-HM-002	1	CATALYTIC REACTOR ELECTRICAL HEATER	300	500	250	2961	g/h	500 / -5	25 / 480	6	4.5
350-VF-001	1	CATALYTIC REACTOR	70	-	180	2961	g/h	420 / -5	480	6 / FV	4
350-XZ-002	1	CATALYTIC STAGE PERMEATOR	63 (1)	-	1000 (1)	2961.04	g/h	420 / -5	400	6 / FV	1.8 ret. side / 0.1 perm. side
350-HC-009	1	SECOND STAGE RETENTATE COOLER	300	400	250	2800	g/h	400 / -5	400 / 25	6	1.8
350-KP-004A/B	2	RETENTATE RECYCLE COMPRESSOR	90 (1)	300 (1)	-	1.4053	Nm ³ /h	400 / -5	25 (5) / 191 (d)	6	1.3 (5) / 4 (d)
350-KC-004A/B/C/D	4	SECOND STAGE SCROLL PUMP	180 (1)	253 (1)	-	0.361	Nm ³ /h	400 / -5	400	4.5 / FV	0.1 (5) / 1 (d)
350-KP-004A/B	2	CATALYTIC STAGE PERMEATOR	90 (1)	300 (1)	-	0.361	Nm ³ /h	296 / -5	25 (5) / 276 (d)	5	1 (5) / 3 (d)

6 Inventory minimization plays a critical role in meeting safety standards and containment measures within power plant operations.

