


(1) The accomplishment of the engineering design activities of IFMIF/EVEDA: The European-Japanese project towards a Li(d,xn) fusion relevant neutron source by Juan Knaster* on behalf of IFMIF/EVEDA family

(2) Evaluation of Li Target Facility of IFMIF in the IFMIF/EVEDA Project by Eiichi Wkai (JAEA) on behalf of IFMIF/EVEDA family



* Absent in FEC 2014 due to unsurmountable difficulties in obtaining the VISA



IFMIF/EVEDA

IFMIF:

International Fusion Materials Irradiation Facility

EVEDA:

Engineering Validation & Engineering Design Activities

Article 1.1 of Annex A of the BA Agreement
mandates IFMIF/EVEDA

...to produce **an integrated engineering design of IFMIF** and the data necessary for future decisions on the construction, operation, exploitation and decommissioning of IFMIF, and **to validate continuous and stable operation of each IFMIF subsystem**

(Signed in February 2007, Entered into force on June 2007)



IFMIF through all technical steps

IFMIF evaluation has successfully passed through all needed key steps as below:

✓ Conceptual Design Activity (CDA) phase in 1996

As a joint effort of the EU, Japan, RF and US

✓ Conceptual Design Evaluation (CDE) report in 1998

Towards a design simplification and cost reduction


✓ The Conceptual Design Report (CDR) in 2004

Co-written by a committee of EU, Japan, RF, US

✓ The final Phase of **EVEDA** within BA activities from 2007

As an efficient **risk mitigation exercise** to face the construction on cost and schedule timely with the world needs for a fusion relevant neutron source


IFMIF Concept



**125 mA CW deuterons at 40 MeV
collide on a liquid Li screen
flowing at 15 m/s**

**A flux of neutrons of $\sim 10^{18} \text{ m}^{-2}\text{s}^{-1}$
is generated in the forward direction
with a broad peak at 14 MeV
and irradiate three regions
>20 dpa/y in 0.5 liters
>1 dpa/y in 6 liters
<1 dpa/y in 8 liters
Materials will be tested in the PIE**

Availability of facility >70%






A Fruitful International Collaboration

IFMIF/EVEDA

A fruitful Japanese- European
International collaboration under the BA Agreement
with 7 countries involved
with the respective main research labs in Europe
and main universities in Japan





Two Work Packages

EVEDA Phase



presents two parallel work packages

EDA Phase

Engineering Design Activities

EVA Phase

Engineering Validation Activities







Design of IFMIF

The Design of IFMIF is broken down to 5 facilities

Objective of Validation activities

- Accelerator Facility
- Lithium Target Facility
- Test Facility
- Post-irradiation and Examination Facility
- Conventional Facilities





EVA Phase Advancing Successfully

ISSN 0029-5518



nuclear fusion

Volume 53 Number 11 November 2013
Co-published and edited by the International Atomic Energy Agency and IOP Publishing

Special Topic
IFMIF: overview of the validation activities
J. Knaster, F. Arbeiter, P. Cara, P. Favuzza, T. Furukawa, F. Groeschel, R. Heidinger, A. Ibarra, H. Matsumoto, A. Mosnier, H. Serizawa, M. Sugimoto, H. Suzuki and E. Wakai

Online: iopscience.org/nf



IOP Publishing
International Atomic Energy Agency, Vienna

IOP PUBLISHING and INTERNATIONAL ATOMIC ENERGY AGENCY
Nucl. Fusion 53 (2013) 116001 (18pp) NUCLEAR FUSION
doi:10.1088/0029-5515/53/11/116001

SPECIAL TOPIC

IFMIF: overview of the validation activities

J. Knaster¹, F. Arbeiter², P. Cara³, P. Favuzza⁴, T. Furukawa⁵, F. Groeschel⁶, R. Heidinger⁷, A. Ibarra⁸, H. Matsumoto¹, A. Mosnier⁹, H. Serizawa⁷, M. Sugimoto⁸, H. Suzuki⁸ and E. Wakai⁹

¹ IFMIF/EVEDA Project Team, Rokkasho, Japan
² KIT, Karlsruhe, Germany
³ F4E, Garching, Germany
⁴ ENEA, Brasimone, Italy
⁵ JAEA, Oarai, Japan
⁶ CIEMAT, Madrid, Spain
⁷ Osaka University, Japan
⁸ JAEA, Rokkasho, Japan
E-mail: juan.knaster@ifmf.org

Received 16 January 2013, accepted for publication 7 June 2013
Published 11 September 2013
Online at stacks.iop.org/NF/53/116001

Abstract
The Engineering Validation and Engineering Design Activities (EVEDA) for the International Fusion Materials Irradiation Facility (IFMIF), an international collaboration under the Broader Approach Agreement between Japan Government and EURATOM, aims at allowing a rapid construction phase of IFMIF in due time with an understanding of the cost involved. The three main facilities of IFMIF (1) the Accelerator Facility, (2) the Target Facility and (3) the Test Facility are the subject of validation activities that include the construction of either full scale prototypes or smartly devised scaled down facilities that will allow a straightforward extrapolation to IFMIF needs. By July 2013, the engineering design activities of IFMIF matured with the delivery of an Intermediate IFMIF Engineering Design Report (IIEDR) supported by experimental results. The installation of a Linac of 1.125 MW (125 mA and 9 MeV) of deuterons started in March 2013 in Rokkasho (Japan). The world's largest liquid Li test loop is running in Oarai (Japan) with an ambitious experimental programme for the years ahead. A full scale high flux test module that will house ~1000 small specimens developed jointly in Europe and Japan for the Fusion programme has been constructed by KIT (Karlsruhe) together with its He gas cooling loop. A full scale medium flux test module to carry out on-line creep measurement has been validated by CRPP (Villigen).
(Some figures may appear in colour only in the online journal)

1. Introduction
Inelastic collisions of neutrons with the nuclei in the structural materials over the threshold incident energy of around 3 MeV will transmute heavy nuclei, which can decay releasing p⁺- and α-particles. In turn, the elastic collisions are measured by NRT displacements per atom (NRT dpa) [1] with a cross section inversely proportional to the average displacement energy threshold for production of a Frenkel vacancy-interstitial atom defect pair in the material. Not all of the materials will present the same NRT dpa under the same neutron bombardment, neither will all areas inside the reactor vessel undergo the same flux and spectrum of neutrons. In addition, NRT dpa do not take into account the time-evolution

0029-5515/13/116001-18\$33.00 © 2013 IAEA, Vienna Printed in the UK & the USA

J. Knaster et al., *IFMIF: overview of the validation activities*, Nuclear Fusion 53 (2013) 116001 (18 pp)



Main Design Improvements from CDR

(CDR: Comprehensive Design Report)

- ✓ Alvarez-type Drift Tube Linac replaced by a Superconducting RF Linac
Reduction in beam losses and operation costs
- ✓ Configuration of the Test Cell changed
irradiation modules have no more a shielding function
Improved irradiation flexibility and the reliability of the remote handling equipment
- ✓ Quench Tank of the Lithium loop re-located outside the Test Cell
Reduction of tritium production rate and simplification of maintenance processes
- ✓ Maintenance strategy modified
Allowing a shorter yearly stop of the irradiation operations
and a better management of the irradiated samples.

Mario Pérez and the IFMIF/EVEDA Integrated Project Team
The Engineering Design Evolution of IFMIF: from CDR to EDA Phase

SOFT 2014



Risk Analysis

Project Risk Register



Exposure
 0-3 = Trivial
 4-6 = Minor
 10-16 = Substantial
 17-25 = Intolerable

Probability and Impact Matrix

IFMIF RISK ANALYSIS
 BA_D_242P5R v1.0

IFMIF RISK ANALYSIS

Abstract

The present document briefly describes the methodology used for the IFMIF risk analysis and reports the results obtained.

	Name	Affiliation
Author	Mario Perez	IFMIF/EVEDA PT
Co-Author	Angel Bourra	CIEMAT
Reviewer(s)	Roland Heidinger Shigeru O'Hira	F4E JAEA
Approver	Juan Knaster	IFMIF/EVEDA PL

Page 1 of 6

Risk Reference Number (ID)	Description	Likelihood Rating 1 to 5	Impact Rating			Exposure	Risk Management Strategy	Description of Action Required
			Technical	Schedule	Cost			
1	Technological feasibility of running low energy hadrons over 100 mA in CW higher than expected losses jeopardizing hands-on maintenance	2	4	4	4	8	Mitigate	Feasibility is to be proven in IFMIF/EVEDA Phase
2	Injector will not provide the full current (140 mA) with less than 0.3 mmmrad emittance value	3	2	3	4	12	Mitigate	Technology upgrade to be developed for beam formation and guidance elements
3	RFQ missing to reach 90% transmission factor	2	3	3	2	6	Accept	Run at reduced current to maintain emittance value
4	MEBT's bunchers not capable to match the beam twiss parameters with the SRF Linac	2	3	2	3	6	Accept	Run at reduced current to reduce total beam losses and dose rates
5	RFQ missing to reach 90% transmission factor	3	3	2	3	9	Accept	Run at reduced current to reduce total beam losses and dose rates in RFQ
6	Excessive losses in the Scrapers	1	2	3	2	3	Mitigate	Enlarge scraper filter window to reduce loss at the cost of beam profile at target
7	Low-β cavities not able to manage high beam currents	2	4	4	4	8	Mitigate	Feasibility is to be proven in IFMIF/EVEDA Phase
8	Quenching on the cavities before nominal accelerating field is reached	1	4	5	5	5	Mitigate	Feasibility is to be proven in IFMIF/EVEDA Phase
9	Tuning of the accelerator based on micro-halo monitors is not effective	2	3	3	3	6	Transfer	Use alternative beam diagnostics
10	Operation of 8 cavities cryomodule is not reliable enough	3	4	3	3	12	Mitigate	Reliability is to be proven in IFMIF/EVEDA Phase
11	High-β cavities not able to manage high beam currents	1	4	4	4	4	Accept	Run at reduced beam currents
12	HEBT fails to properly shape the beam at the target	2	3	2	2	6	Accept	Run with a degraded beam profile at the target
13	Non-efficient beam profile monitoring	2	3	2	2	6	Accept	Run with a degraded beam profile at the target
14	Unforeseen phenomena in the D+ beam - Li free surface interaction	2	5	5	3	10	Prevent	Plan an experimental test with protons at the very early stage of commissioning
15	Excessive corrosion rate in the nozzle of the target	3	4	4	4	12	Mitigate	Reduce the operation time while improving the mechanical perfection of the nozzle
16	Height of Li waves over specified values	3	3	3	3	9	Mitigate	Reduce slightly beam energy if critical margin of Bragg peak is exceeded
17	Impurity levels (H, N and others) over specified values in the flowing lithium	4	3	4	4	16	Prevent	Plan an experimental verification of the purification system at the very early stage of commissioning
18	Lack of diagnostic systems for Li flow characterization	3	3	3	3	9	Mitigate	Reduce slightly beam energy if critical margin of Bragg peak is exceeded
19	Uncertainty on the backplate lifetime due to unknown radiation effects on material properties	4	4	3	3	16	Mitigate	Foresee several spare backplate/target assembly components for early replacement
20	Maintenance procedure of the Target Assembly longer than expected	3	2	4	4	12	Mitigate	Procedure is to be proven in IFMIF/EVEDA Phase
21	Neutron flow pattern missing to meet specifications	2	3	3	2	6	Accept	Run with degraded neutron flux pattern
22	Non-efficient neutron profile monitoring	3	3	2	2	9	Accept	Use information from neutronic analysis
23	Loss of HFTM temperature control (heaters and/or Cooling system) during one irradiation campaign	2	4	5	4	10	Prevent	Plan an experimental verification of the heating system at the very early stage of commissioning
24	Uncertainty on the PCPs lifetime	2	4	3	3	8	Mitigate	Foresee several spare PCP assembly components for early replacement
25	Maintenance procedure in the Test Cell longer than expected	4	4	5	3	20	Mitigate	Reduce number of second-order Test Module limits, extend operation time beyond specifications
26	Crane failure in the Access Cell during maintenance activities	2	3	3	3	6	Prevent	Plan an experimental verification of the crane system at the very early stage of commissioning
27	Small specimen testing techniques do not satisfy testing standards	2	3	3	3	6	Mitigate	Promote Standardisation process to cover techniques applied
28	Availability of the IFMIF plant does not reach the values predicted by RAM analysis	3	3	5	4	15	Mitigate	Reduce operation parameters for accelerator to enhance the reliability of the accelerator
29	Major difference between calculated and experienced radioactivation	2	4	5	4	10	Mitigate	Level of radioactivation is to be proven in IFMIF/EVEDA Phase

Likelihood Rating:

- 1 = Very Unlikely = 0 - 20%
- 2 = Unlikely = 20% - 40%
- 3 = Likely = 40% - 60%
- 4 = Very Likely = 60% - 80%
- 5 = Near Certain = 80% - 100%

Impact Rating

- Technical**
- 1 = Minimal or no degradation on performances
 - 2 = Acceptable, marginal reduction on performances
 - 3 = Significant threat to facility mission
 - 4 = Serious threat to facility mission
 - 5 = Catastrophic threat to facility mission
- Schedule**
- 1 = Minimal or no impact
 - 2 = Marginal impact of a key milestone (3-6 weeks delay)
 - 3 = Significant impact on a key milestone (1-3 months delay)
 - 4 = Serious impact on a key milestone (3-6 months delay)
 - 5 = Unacceptable impact on a key milestone (> 6 months delay)

- Cost**
- 1 = Negligible impact (<1% estimated cost)
 - 2 = Potential impact of 1-10% on estimated cost
 - 3 = Potential impact of 10% - estimated cost <20%
 - 4 = Potential impact of 20% - estimated cost <40%
 - 5 = Potential impact >40% on estimated cost



IFMIF, a fusion relevant neutron source for material irradiation current status



J. Knaster^{a,*}, S. Chel^b, U. Fischer^c, F. Groeschel^c, R. Heidinger^d, A. Ibarra^e, G. Micciche^f, A. Möslang^g, M. Sugimoto^h, E. Wakai^h

^a IFMIF/EVEDA Project Team, Rokkasho, Japan

^b CEA, Saclay, France

^c KIT, Karlsruhe, Germany

^d FZJ, Garching, Germany

^e CIEMAT, Madrid, Spain

^f ENEA, Brasimone, Italy

^g JAEA, Rokkasho, Japan

^h JAEA, Oarai, Japan

ARTICLE INFO

Article history:
Received 29 April 2014
Accepted 27 June 2014
Available online 7 July 2014

ABSTRACT

The d-Li based International Fusion Materials Irradiation Facility (IFMIF) will provide a high neutron intensity neutron source with a suitable neutron spectrum to fulfil the requirements for testing and qualifying fusion materials under fusion reactor relevant irradiation conditions. The IFMIF project, presently in its Engineering Validation and Engineering Design Activities (EVEDA) phase under the Broader Approach (BA) Agreement between Japan Government and EURATOM, aims at the construction and testing of the most challenging facility sub-systems, such as the first accelerator stage, the Li target and loop, and irradiation test modules, as well as the design of the entire facility, thus to be ready for the IFMIF construction with a clear understanding of schedule and cost at the termination of the BA mid-2017. The paper reviews the IFMIF facility and its principles, and reports on the status of the EVEDA activities and achievements.

© 2014 Elsevier B.V. All rights reserved.

1. Introduction

A fusion relevant neutron source is a more than three decades old pending step for the successful development of fusion energy. Safe design, construction and licensing of a nuclear fusion facility by the corresponding Nuclear Regulatory agency will demand the understanding of the materials degradation under the neutrons irradiation during the life-time of the fusion reactor. The deuterium–tritium nuclear fusion reactions will generate neutron fluxes in the order of $10^{18} \text{ m}^{-2} \text{ s}^{-1}$ with an energy of 14.1 MeV. The first wall of the reactor vessel, a complex combination of layers of different materials will be most exposed undergoing potentially $>15 \text{ dpa}_{\text{NET}}$ per year of operation [1,2]. It is indispensable that the plasma facing components can withstand the operational conditions without degradation of their mechanical and physical properties beyond defined thresholds driven, not only by nuclear safety reasons, but also by investment protection aspects. The main path for increasing the efficiency of power plants consists of raising the

temperatures of transformation processes and energy transmission a period long enough to make a power plant economically interesting. Qualifying suitable materials at equivalent irradiation conditions as in a fusion reactor is a first step that concurrently with the understanding of the materials behaviour will lead, in hand with computations techniques, to the development of new materials capable of making the operation of a nuclear fusion power plant viable.

2. Why a fusion relevant neutron source?

Degradation of materials under neutron irradiation is a phenomenon anticipated in 1942 by Wigner [3]. Nuclei are transmuted through nuclear interactions with the incident neutrons to stable or radioactive nuclei via (n, α) , (n, p) , (n, γ) or other reaction channels. Through elastic and inelastic collisions neutrons initiate primary recoil knock-on atoms (PKA) [4] with a cascade of Frenkel vacancy–interstitial pairs with threshold energies as low as 40 eV for Fe and Cr [5]. The damage in the microstructure of the metal contributes to material degradation through the internal pressure of accumulated gas molecules resulting from the nuclear reactions.

* Corresponding author.
E-mail address: juan.knaster@ifmif.org (J. Knaster).

<http://dx.doi.org/10.1016/j.jnucmat.2014.06.051>
0022-3115/© 2014 Elsevier B.V. All rights reserved.

Possible inquiries please
juan.knaster@ifmif.org

or at

+81 (0) 175 71 66 35

www.ifmif.org

Wikipedia

J. Knaster et al., *IFMIF, a fusion relevant neutron source for material irradiation current status*,
Journal of Nuclear Materials 453 (2014) 115–119


Evaluation of Li Target Facility of IFMIF in the IFMIF/EVEDA Project

by Eiichi Wkai (JAEA) on behalf of IFMIF/EVEDA family




**EVEDA Li Test Loop
constructed in JAEA-Oarai**

IFMIF Liquid Lithium Target Concept



- D⁺-Li stripping reaction generates high intense neutrons to simulate fusion irradiation conditions.
- High-speed liquid Li flow along concave back plate is selected as IFMIF target to handle a high heat load of 10MW D⁺ beams.



Major Requirements for Li Target in IFMIF

- Averaged heat flux : 1 GW/m²
- **Jet velocity** : **15 m/s (range 10-20 m/s)**
- **Jet thickness/Width** : **0.025 m/0.26 m**
- **Surface wave amplitude** : **< +/- 1 mm**
- **Initial (inlet) Li temperature: 250 °C**
- **Vacuum pressure** : **10⁻³ - 10⁻² Pa near Li free surface**


Main Missions of EVEDA Li Test Loop (ELTL)

- Validation of **stable long-time operation of a high-speed free-surface liquid Li** simulating IFMIF target.
- Validations of **diagnostics on the Li flow** and impurity control systems for a Li loop.

Engineering Validation Research

Construction, operation and tests of EVEDA Li test loop (installed at Oarai)

- (1) Functional tests of each equipment
 - (2) Tests of high-speed fluid with a free surface under vacuum
 - (3) Long-duration tests
- (the EU: Cavitation test, etc..)



Diagnostics

- Wave height measurement of high-speed Li flow
- Applicability evaluation of diagnostics by a Li loop at Osaka Univ.
- Assistance analysis by a water test loop

Li purification system

- Removal of impurities in Li, impurity monitors

Remote handling


- Replacement of the integrated target assembly (Japan).
- Replacement of only the backplate (the EU).

Erosion/Corrosion

- The tests for 1000 to 8000 hours in a small Li loop of the EU (F82H, Eurofer 97)


Li Safety handling

- Li handling technology, fire extinguishing testing




Engineering Design

Construction, operation and tests of EVEDA Li Test Loop (ELTL) – Schedule -



World largest liquid Li test loop constructed by JAEA in Oarai-site (Nov. 2010)



Confinement Vessel for Lithium flowing with free surface in target assembly

Vacuum pump for Target

Air Duct of Heat Exchanger

Heat Exchanger of Air cooling type

Vacuum pump

Li Dump Tank

20 m in Height

Third floor: Target vessel, A part of Quench Tank, etc.

Second floor: Li sampler, Heat Exchanger, Cavitation sensor Cabinet

First floor: EMP, Cold trap, Cavitation Sensor, etc.

Under ground level: Li dump tank. (2.5 ton Li (5000 L))

■ This height was needed to prevent the occurrence of cavitation in Electro-Magnetic Pump.

Table.: Model and major specifications of the instruments

	Instrument	Model, Mfr	Major spec.
Flow rate	EMF(Electro-magnetic flow meter)	Sukegawa electric Co., Ltd.	Range: 0 ~ 3000 L/min (operational range) Accuracy (2 σ): +/-55.8 [L/min] or 1.86 % FS*
	Pressure gauge	PTU-S, Swagelok	Range: - 0.1 to 0.3 MPaG Accuracy: +/- 0.5 % FS
Target Flow Obser.& Meas.	Cold- cathode Pirani gauge	M-360CP-SP/N25, Cannon Anelva Corp.	Range: 5 x 10 ⁻⁷ to 1 x 10 ⁵ (Pa) Accuracy: +/- 30 % RD**
	Video camera	HVR-Z7J, Sony	Record format: HDV1080/60i
	Digital still camera	D800 (Lens: AS Nikkor 28-300 mm), Nikon	Number of pixels: 36.3 M
	Laser Distance meter	Optical Comb Absolute Distance Meter ML-5201D1-HJ, Optical Comb, Inc.	See: Next page



* FS: Full Scale, **RD: Reading

The flow rate and pressure were recorded in a control PC in the central control room every one second. On the other hand, the appearance of the Li target was monitored and recorded by a video camera and a digital camera.

Item	Value (IFMIF condition)	
Mean Li jet speed U_m [m/s]	10, 15, 20 (10 ~ 16)	
Inlet Li temperature [°C]	250 (or 300)	
Vacuum pressure P_v [Pa]	$1.6 \sim 4.0 \times 10^{-3}$ ($10^{-3} \sim 10^{-2}$)	1.6 ~ 2.1
Measurement positions [mm]*	At Y = 0 mm: $-50 \leq X \leq 50$ At X = 0 mm: $-50 \leq Y \leq 50$ ($-25 \leq X \leq 25$ and $-20 \leq Y \leq 20$)	Whole measurement range: $-50 \leq X \leq 50$ and $-50 \leq Y \leq 50$ ($-25 \leq X \leq 25$ and $-20 \leq Y \leq 20$)
Sampling frequency [kHz]	500	
Data recording time [sec]	60 (one-turnover circulation time of approximately 60 s at 15 m/s)	
Laser wavelength [nm]	1550	
Laser spot diameter [mm]	0.13 (determined based on the preliminary result)	
Measurement error [mm] (Evaluated experimentally)	<u>0.04 (for target thickness)</u> <u>0.02 (for wave height)</u>	

*The intervals of measurement positions are 10 or 15 mm for the X direction and 5 mm for the Y direction. ²¹


$V = 15.1 \text{ m/s}$, $P = 1.3 \times 10^{-3} \text{ Pa}$
 $T = 250 \text{ }^\circ\text{C}$



- (a) Flow straightener
- (b) Double contraction nozzle
- (c) Target flow channel (back plate)
- (d) Viewing port


Time-averaged thickness of Li flow -3D image -

15 m/s, 3 Pa, 250 °C



Wave height distribution

15 m/s, 10⁻³ Pa, 250 °C



Laser-probe method

- **Laser-distance meter (Optical Comb Inc.)**
Time-of-flight (TOF) measurement
- **Analysis method:**
Zero-up crossing method
for average thickness and statistical properties of wave height



- Average thickness :**
 - 26.08 +/- 0.08 mm (1σ) at B/C
 - Nonuniformity (max.-min.) is 0.16 mm
- Wave amplitude (= height/2) :**
 - Mean : 0.26 +/- 0.02 mm (1σ) at B/C
 - 99.7 % are less than 1 mm (requirement)
 - Weibull Distribution

T. Kanemura, H. Kondo et al., "Measurement of Li-target thickness in the EVEDA Li Test Loop", To be published in Fus. Eng. Des.

- Period: 1 month (2 – 26 Sep. 2014)
- Condition: Li target (15 m/s, 300 – 250 °C, 120 kPa) in parallel with the purification system (cold trap at 200 °C)

- ✓ Stable Li target throughout the continuous operation
- ✓ Accumulated time of Li target operation > 1000 hours

(At present it is continuing the Li flowing up to end of Oct. 2014)



Long-time stability of the Li target was successfully demonstrated.

Li Target Validation Tests - Summary -

- ✓ Validation of the Li target was the highest priority subjects for the Li target system of the IFMIF/EVEDA project. To achieve this goal, we designed and constructed the ELTL, and produced a stable Li target that complies with IFMIF requirements.

1. The Li target in the IFMIF conditions (250 °C, 15 m/s, 10^{-3} Pa) and its stability were successfully demonstrated.


- Average thickness: 26.08 ± 0.08 mm (1σ)
- Mean wave amplitude: 0.26 ± 0.02 mm (1σ)
- Maximum wave amplitude: 1.45 ± 0.14 mm (1σ)

The maximum wave amplitude is very few over the design requirement of 1 mm, and 99.7 % of the total wave components are within the requirement. Therefore, we confirmed that the Li target of the current design was quite stable and satisfies the design requirement. We finally validated the Li target stability.

2. Continuous long-term operation of the Li target was conducted (continuous operation: 1 month, accumulated time: >1000 h).

*(The validation operation of the Li test loop is continuing up to the end of Oct. 2014.)*²⁵


Thank you for your attention



Specification of ELTL and IFMIF LF

Items	ELTL	IFMIF Lithium Facility
Nozzle design	Double-contraction	Double-contraction
Back wall	Concave (316L)	Concave (RAFM)
Jet thickness [mm]	25 mm	25 mm
Jet width [mm]	100 mm	260 mm
Max. jet velocity / surface pressure [m/s]	20/10 ⁻³ Pa to atmospheric pressure	15 (max.16)/ <10 ⁻² Pa
Max. flow rate [L/s]	50 L/sec	133 L/sec
Temperature [°C]	250-350°C	250-300°C
Li inventory [m ³]	5.0 m ³	9 m ³
Status	In Operation	Design stage

- To perform corrosion/erosion tests at constant temperature (reference 350° C) and velocity (reference 16 m/s in test section) under the purification control for Li with less than 30 wppm N
- To test lithium purification and impurities monitoring systems




Material	Exposure [h]
F82H/	~ 1000
Eurofer	~ 2500
	~ 3500



Design Specification of Proto Type of EVEDA Lithium test loop (ELTL)

Li inventory	2.5 tons (5000 l)
Li flow rate	3000 L/min (max.)
EM flow meter range	± 3000 L/min
Li flow velocity in Target	≤ 20 m/s
Material	S.S. 304 for pipe, 316L for back-plate
Li temp.	250-350 °C
Design temp.	400 °C
Design pressure	10 ⁻³ Pa to 0.75 MPa G



(a) Flow Straightener

- A honeycomb for removing large scale turbulence.
- Three perforated plates for flattening velocity distribution.

(b) Contraction Nozzle

- Two-step contraction, contraction ratio is 10. (250 mm to 25 mm in thickness)

To obtain flow velocity up to 20 m/s.

(c) Target Flow Section (back plate)

- i) *Flow Width and Thickness : 100 and 25 mm*
- ii) *Viewing Ports: Two Ports*

Measurement for Li free surface in ELTL (Non-Contact Method – Developed Laser distance meter)




Fig. Interference condition of laser

The present laser condition:

- Spot diameter: 0.1 mm (MFD)
- Laser incident angle: 0.85°





Fig. Slope angle α (solid line) with sine curve y (dashed line)

$$y = A \sin(2\pi x / \lambda) \quad A: 0.28 \text{ mm}$$

$$\alpha = \tan^{-1}(dy / dx) \quad \lambda: 4 \text{ mm [3]}$$

The incident laser is returned to the laser head from the region of 0.044 mm. This means **62 % of the total energy is returned** (the laser energy is distributed to normal distribution), which is considered to be large enough for a significant signal.

Laser Distance Meter



- The target stability limit: 2 mm in wave height H
 - Mean wave height $\bar{H} \approx 0.5$ mm for all data
 - Thus, nondimensional stability limit: $H/\bar{H} \approx 4$
- 99.7 % of the total wave components is within the limit!**

The solid red line denotes the **Rayleigh distribution**,


$$P(H) = \frac{\pi H}{2 \bar{H}} \exp \left[-\frac{\pi}{4} \left(\frac{H}{\bar{H}} \right)^2 \right] \quad (1)$$

The dashed blue line denote the **Weibull distribution**, the “parent” distribution of the Rayleigh distribution,


$$P(X) = \frac{k}{\lambda} \left(\frac{X}{\lambda} \right)^{k-1} \exp \left[-\left(\frac{X}{\lambda} \right)^k \right] \quad (2)$$

Nondimensional wave height distribution at $P_v = 1$

where $k > 0$ is the shape parameter and $\lambda > 0$ is the scale parameter of the distribution. When $k = 2$ and $\lambda = \sqrt{4/\pi}$, Eq. (2) is reduced to Eq. (1). The parameter of the fitting curve is $k = 1.73 \pm 0.03$, $\lambda = 1.07 \pm 0.02$.



The area corresponding to the IFMIF beam footprint
 $(-25 \leq X \leq 25 \text{ and } -20 \leq Y \leq 20)$




Three-dimensional plot of the average thickness of the Li target at $U_m = 15 \text{ m/s}$ at $P_v = 1.8 \text{ Pa}$.
 (Black symbols denote measurement data)


Un-uniformity inside the beam footprint was

- 0.16 mm along the Y (spanwise) direction,
- 0.10 mm along the X (streamwise) direction.

The Li target is adequately smooth on average.



Average thickness distribution along the Y (spanwise) direction at $X = 0$.



Average thickness distribution along the X (streamwise) direction at $Y = 0$.

Presented by T. Kanemura in SOFT2014

Statistics of measurement results obtained at the beam center $(X, Y) = (0, 0)$ under the IFMIF condition.

U_m [m/s]	10	15	20	Design requirement
N^*	5	6	2	-
A_{mean} [mm]**	0.23 ± 0.02 (1σ) ***	0.26 ± 0.02 (1σ) ***	0.24 ± 0.01 (1σ) ***	1 mm
A_{max} [mm]**	1.50 ± 0.11 (1σ) ***	1.45 ± 0.14 (1σ) ***	1.66 ± 0.10 (1σ) ***	
η_{mean} [mm]	25.73 ± 0.07 (1σ) ***	26.08 ± 0.08 (1σ) ***	26.15 ± 0.08 (1σ) ***	25 mm

N : the number of the data samples, A_{mean} : Mean wave amplitude, A_{max} : Maximum wave amplitude,

η_{mean} : Average thickness

*The data were obtained on different days to check reproducibility.

**Amplitude A is half wave height ($A = H/2$).

***Measurement uncertainty includes variation of measured data itself and measurement error.

The Li target of the current design is quite stable and satisfies the design requirement.

Purposes of impurity reduction


- suppression of corrosion (C, N, O)
- suppression of erosion (H(?), C, O)
- reducing of radio-activity of Li (T(H,D))
- preventing Y from degradation (N, O)

Total content of H isotope in Li	(≤ 10 wppm)
T content in Li	(≤ 1 wppm)
N content in Li	(≤ 10 wppm)
O content in Li	(≤ 10 wppm)

C, O: solubility is small enough to use cold trap.

N: Formation of Li-Cr-N is one of the most serious corrosion for S.S. (>60~70wppmN)
 YN is very stable, which degrades hydrogen getting efficiency.
 ⇒Titanium react with N even N in Li is less than 1wppm

H: Hydrogen distribution ratio between Y/Li is very large.
 However, Yttrium easily react with N and O in Li



Solubility of H, C, N, O in Li