



**FUSION
FOR
ENERGY**

Progress Status of the Activities in EU for the Development of the ITER Neutral Beam Injector and Test Facility

Antonio Masiello

G. Agarici¹, D. Boilson², T. Bonicelli¹, H. Decamps², U. Fantz³, P. Franzen³, J. Graceffa², B. Heinemann³, R. Hemsworth², D. Marcuzzi⁴, F. Paolucci¹, M. Simon¹, V. Toigo⁴, P. Zaccaria⁴

¹*Fusion for Energy, C/ Josep Pla 2, 08019 Barcelona, Spain*


²*ITER Organization, Route de Vinon sur Verdon, 13115 Saint Paul-lez-Durance, France*

³*Max-Planck- Institut für Plasmaphysik (IPP) - D-85740 Garching, Germany*

⁴*Consorzio RFX, Euratom-ENEA Association, C.so Stati Uniti 4, I-35126, Padova, Italy*

- ✓ **The ITER neutral beam and the test facility**
- ✓ **The development of the beam source**
 - Results of the ELISE experiment
 - Status of the SPIDER experiment
 - Design and R&D of the MITICA beam source
- ✓ **The development of the beam line components**
- ✓ **The ITER Heating Neutral Beam front end components**
- ✓ **Conclusions**

The ITER HNB






The Neutral Beam Test Facility

The Neutral beam test facility, established in Padua – Italy at the PRIMA site , provides a comprehensive strategy to mitigate technical and operational risks for the NB systems at ITER

Phase 1: The NBTF design – **Being COMPLETED!**

Phase 2: The NBTF Construction – **On-going**

Phase 3: HNB Design Operation - technological/scientific exploitation of NBTF with the aim to achieve the final design and specifications for the HNB



The beam source development




FUSION
FOR
ENERGY


ELISE (Garching Germany) - half-size ITER-type source with beam extraction to assess the possibility of achieving ITER like parameters with a source filling pressure of ~ 0.3 Pa and spatial uniformity at full ITER current density

SPIDER (at PRIMA site) - Full size ITER source (HNB and DNB), full current extraction at full DNB extraction voltage (100 kV) and full ITER pulse length


MITICA (at PRIMA site) - Full size, full voltage, full power, full pulse length ITER beam-line



1 Driver – IPP
prototype source
 $0.52 \times 0.26 \text{ m}^2$



4 Drivers – ELISE – IPP
 $1.0 \times 0.9 \text{ m}^2$



8 Drivers – SPIDER and
MITICA (and the HNB/DNB)
 $1.9 \times 0.9 \text{ m}^2$


The ELISE experiment

Main parameters


Isotope	H ⁻ , D ⁻
Extraction area	1000 cm ²
Total acc. voltage	60 kV
Extraction voltage	<12 kV
Ion current	20 A
RF power	2 x 180 kW
Plasma on time	3600 s
Extraction	10 s every 150-180 s

Target operation parameters

Extracted current	330 A/m ² (H ⁻)
density	250 A/m ² (D ⁻)
Extracted electrons/ion	< 1
Source pressure	0.3 Pa
Beam uniformity	10%




The ELISE experiment




The ELISE results

Parameter	Unit	H	D	
Pulse #	-	#6541	#7761	#7801
Pulse length	s	10	3.4	3.3
Extracted Curr. Dens.	A/m ²	256	177	195
Accelerated Curr. Dens.	A/m ²	203	144	154
Electron/Ion ratio	-	0.66	0.65	1.06
Filling Pressure	Pa	0.29	0.33	0.33
Extraction Volt.	kV	9.8	9.5	9.5
Norm. Perveance	-	0.176	0.184	0.205
RF power	kW	2X105	2X90	2X105
Bias Current	A/m ²	55	55	55
PG current	kA	2.2	4.0	4.0


H⁻ operation



D⁻ operation



The ELISE experiment



CCD view inside of the ion source

Light starts inside the drivers where the starting filaments are ignited and then propagates in the expansion chamber

Infrared view of the calorimeter

A thick water cooled copper plate in which a chessboard like pattern has been machined allowing the beam footprint to be reconstructed




- ✓ **Quick source conditioning** with an electron/ion ratio well below 1, no need for a daily conditioning (absolute valve separates the beam source from the main tank).
- ✓ **Linear scaling of the RF power with the current density.** A total power of 75kW/driver is estimated for the required current density in H (330 A/m²). This should be OK for driver operation.
- ✓ The best performance **in H** was achieved at the required pressure of 0.3Pa with a **high reproducibility**.
- ✓ **D operation suffers from a large variation of the extracted electron currents** and from the deterioration of the grid HV holding, when the Cs influx between pulses is too large.
- ✓ **Enhanced electron current in D** has to be still properly understood, one possible cause could be the **reservoir of Cs accumulated** during the H campaign that are removed during D pulses.

The SPIDER experiment



FUSION
FOR
ENERGY

Species	H, D
P_{beam}	= 4.0 MW
I	= 40 A
V	= 100 kV
T_{pulse}	= 3600 s



SPIDER VV manufacturing




**FUSION
FOR
ENERGY**



Lids positioning system



**One of the
3 electrical
bushing
(120kV)**



Rear lid



**Pumping
module**



Moving system detail

**Beam
source
module**




The SPIDER beam source



FUSION
FOR
ENERGY


- BP = Bias Plate
- PG = Plasma Grid
- EG = Extraction Grid
- GG = Grounded Grid
- ED = Electron Dump




SPIDER BS manufacturing



**FUSION
FOR
ENERGY**




Heterogeneous joint prototypes




CMM verification of the plasma drivers' plate



Steps of the fabrication of the Faraday shields




Machining of the cooling channels on an extraction grid segment



De-waxing check of a Faraday shields back plate



Alumina insulator prototypes



The short pulses calorimeter STRIKE
CFC tiles monitored on the back by infrared cameras

Embedded diagnostics

TCs and Langmuir probes – mainly in the beam source




Interfaced diagnostics:

- Optical emission spectroscopy (beam and ion source)
- Tomography
- CRDS
- Neutrons (GEM detectors)
- IR thermography
- imaging beam
- CCD+IR monitor



The MITICA experiment



FUSION
FOR
ENERGY




Species	H, D
P_{beam}	= 40 MW
I	= 40 A
V	= 1000 kV
T_{pulse}	= 3600 s



The MITICA beam source (1)



FUSION
FOR
ENERGY



- **Beam optics** - maximisation of aperture clearance and minimisation of beamlet divergence
- **Sensitivity analyses** of the effect of the grid misalignment and grid deformation
- **Optimised magnetic field configuration** - as uniform as possible magnetic field
- **Co-accelerated electrons** - Power associated @ accelerator exit <700kW
- **Thermo-mechanics** - power deposited on accelerator grids <2MW
- **Gas pressure profiles** – background gas pressure as uniform across grids and as low as possible
- **Evaluation of the power load** on the rear vertical surface of the ion source due to BSI⁺


The MITICA beam source (2)



FUSION
FOR
ENERGY






Explosive bonding of Mo on CuCrZr – back plates of the ion source




Routing of the water and electrical line including flexible connection for beam source tilting (on and off-axis beam injection)

Remote handling studies of the installation and maintenance. Removal of the screens, cut&weld of coolant lines




The neutraliser and electron dump (NED)



Neutraliser - $0,5 \text{ MW/m}^2$ to 5 MW/m^2 on the leading edges
5,5MW -15 tons

The heat power of the co-accelerated electrons are taken by the **electron dump** (in the front of the NED), whose panels have been optimised with respect to the different aspects: **maximization of the gas conductance** from the Beam Source to the cryogenic pump, **protection of cryogenic panels** from the scattered electrons, **foldable panels** geometry for installation and maintenance.




Butt welding with the ITER vacuum requirements SS to OF copper with the interposition of an Inconel element

The MITICA RID




FUSION
FOR
ENERGY






Electrostatic Residual Ion
Dump ($6\text{MW}/\text{m}^2$)
19MW - 5 tons

Double side
**deep drilling of
2m long**
CuCrZr plates


Enhanced heat
transfer in
subcooled
boiling
conditions
provided with
twisted tapes
as turbulence
promoters



RID beam stop element



The MITICA Calorimeter






Calorimeter (14MW/m²)
18MW- 7tons

Production feasibility of the swirl tubes was validated by bending of CuCrZr tubes into the required shape. Tests confirmed that stress relaxation during beam operation will not occur.

Tube diameter = 20 mm

No. of EB connection per panel = 192


Total EB weld length = 24m



ITER HNB components (Front End components)




FUSION
FOR
ENERGY




Absolute Valve


Stainless Steel Casing
SIC1- (RCC-MR code)
High vacuum




Drift Duct - SIC1 – (RCC-MR code) Stainless Steel Double **Bellows** -
Deep Drilled **liner** CuCrZr



Bellows




Liner



Fast Shutter

Stainless-Steel
Casing SIC1- (RCC-
MR code)– High
Vacuum



Exit Scraper

Stainless Steel Support +
Deep Drilled Panel
CuCrZr
High Vacuum (Non -SIC)

- ✓ Experiments on **ELISE** has shown that the one driver concept can be transferred to an ITER relevant size source
 - Achievement of the required parameters in hydrogen on ELISE seems possible
 - Results of the first operations in deuterium suffer from the difficulty of controlling the co-extracted electrons
- ✓ The fabrication of the **SPIDER beam source is well in progress** after completion of the manufacturing design, which required a long time due to the complexity of the system and the challenging requirements
- ✓ Even more **tight requirements** are being fulfilled in the preparation of the tech specs for the procurement of the **MITICA beam source** and **beam line components**, replicating the HNB ones in almost all details, including RH features.

The development of the core components of the HNB is being pursued putting in place the planned strategy. Having obtained so far encouraging results gives some confidence that the HNB is on track to be developed for the second phase of the ITER experiments.



**FUSION
FOR
ENERGY**

Thank you for your attention

Follow us on:



www.f4e.europa.eu



www.twitter.com/fusionforenergy



www.youtube.com/fusionforenergy



www.linkedin.com/company/fusion-for-energy



www.flickr.com/photos/fusionforenergy