



IAEA FEC 201

Contribution ID: 812

Type: Oral

Assembly Technologies of the Superconducting Tokamak on JT-60SA & JT-60SA TF Coil Manufacture, Test and Preassembly by CEA

Saturday, 22 October 2016 11:25 (20 minutes)

A. The JT-60SA (JT-60 Super Advanced) project is a combined project of Japan's program for national use and the Japan-EU Satellite Tokamak Program collaboration between Japan and the EU fusion community. The main objectives are to demonstrate steady-state high-beta plasma and to support ITER through the optimization of ITER operation scenario. The JT-60SA tokamak device is designed as a superconducting tokamak, which is about half of ITER. This tokamak assembly must allow for the thermal deformations of the superconducting coils at 4 K and 473 K baking for the vacuum vessel (VV) in addition to withstanding electromagnetic and seismic forces. The rigid support method is not able to absorb the thermal contraction and expansion. On the other hand, a high accuracy, below several millimeters, is required for the positioning of the superconducting coils to achieve a magnetic field error under 10^{-4} B_{tor}. Two types of gravity supports are employed for the superconducting coil system and the VV. Both gravity supports are characterized by their flexibility to absorb thermal deformation while maintaining their symmetry about the toroidal axis. In the onsite assembly work, it is important to install these components with high accuracy and adjust them to their design positions. Installation of the VV and pre-positioning of the lower equilibrium field coils have been achieved with high accuracy of a few millimeters using carefully planned assembly technologies, which are the combination of 3D CAD and real-time 3D position measurement by a laser tracker, customization of the joint structures derived from the measurement, and welding taking account of predicted deformations. The assembly measurement precision due to spatial recognition is 0.5 mm in the tokamak hall of 40 meters square. The sector joints of the VV were completed up to 340-degrees. The shrinkage of each weld was predicted from factory manufacturing results and this prediction was improved by the measurement of the shrinkage of each pass during the welding of the joints between sectors. The complete assembly of JT-60SA is expected to be achieved with high accuracy by applying these assembly technologies. The design and manufacturing of these components have been shared by the EU and Japan, and the assembly of these components started on the Naka site in 2013 aiming at the first plasma in 2019.

B. In 2005, when the ITER site decision was made, the French Government decided to participate to the joint Europe-Japan implementation of the so-call "Broader Approach Activities" (BA) in support of the ITER project and DEMO activities [1,2]. The BA comprises the ITER Satellite Tokamak Programme (STP) which consists in upgrading the JT-60U machine into the largest fully superconducting and actively cooled D shaped tokamak JT-60SA before ITER, and in the participation to its scientific exploitation. As collaboration with Fusion for Energy (F4E), the French commitments, in charge of CEA as Voluntary Contributor (VC), are described in the Agreement of Collaboration (AoC) [3]. The CEA contribution related to the Toroidal Field Coil (TFC) procurement is 9 + 1 spare of the 18 + 2 spares TFCs, the whole supporting structures, the TFC Cold Test Facility (CTF) and the TFC pre-assembly. The complementary contribution is in charge of Italy. After the preparation and qualification phases, in these last two years, the industrial production for the procurement of the French contribution to the Toroidal Field Coil manufacture is now well engaged. The first coils were wound and integrated into their casings. The first mechanical structures were produced. These coils were sent to the Cold Test Facility and cold tested for final acceptance before to be assembled with their Outer Intercoil Structures in a dedicated workstation. These assemblies are the first components of the TF magnet which were sent to JAEA. In parallel the following TFC production, qualification and preassembly are ongoing.

Paper Number

FIP/4-1Ra & FIP/4-1Rb

Country or International Organization

Japan

Primary author: Dr SHIBAMA, Yusuke (NATIONAL INSTITUTES FOR QUANTUM AND RADIOLOGICAL SCIENCE AND TECHNOLOGY)

Co-author: Dr DECOOL, Patrick (CEA, IRFM, F-13108 St-Paul-lez-Durance, France)

Presenter: Dr SHIBAMA, Yusuke (NATIONAL INSTITUTES FOR QUANTUM AND RADIOLOGICAL SCIENCE AND TECHNOLOGY)

Session Classification: Transport, Construction and PD

Track Classification: FIP - Fusion Engineering, Integration and Power Plant Design