



IAEA FEC 201

Contribution ID: 108

Type: Poster

Edge- and divertor and plasma behavior in high power high performance double-null plasmas

Wednesday, 19 October 2016 08:30 (4 hours)

We identify major challenges to reducing divertor heat flux in high power, high performance near-double null DIII-D plasmas, while still maintaining sufficiently low density to allow for application of RF heating. The plasmas discussed here are characterized by: $\beta_N \approx 3-4$, $H_{98} \approx 1.5-1.7$, $dR_{SEP} \approx -5$ mm, and P_{IN} up to 20 MW. The scaling of the peak heat flux ($q_{\perp p}$) at the outer target of the primary divertor was proportional to $P_{SOL}^{0.92}$ and $I_p^{0.92}$ in the range $P_{SOL} = 8-19$ MW and $I_p = 1.0-1.4$ MA and is consistent with standard ITPA scaling for single null configurations. Three distinct divertor heat flux reduction techniques were tested. First, the puff-and-pump radiating divertor was less effective in reducing divertor heat flux when β_N was raised to 3.7 than occurred for lower values of β_N and P_{IN} . In the higher β_N case, gas puffing during puff-and-pump resulted in an increase in τ_E and τ_p and led to more rapid fueling of the core. This set an upper limit on the D_2 injection rate that can be tolerated without losing density control, thereby undermining the effectiveness of puff-and-pump. We are investigating how a decrease in ELMing frequency during D_2 injection at higher power and β_N may drive this process. Second, increasing the poloidal flux expansion at the outer target of the primary divertor did not produce the expected reduction in $q_{\perp p}$ that would have been expected from geometrical arguments, e.g., almost doubling the poloidal flux expansion reduced $q_{\perp p}$ by only $\sim 20\%$. Preliminary analysis suggests that cross-field diffusion effects appear to counteract poloidal flux expansion. Third, we show how $q_{\perp p}$ was reduced by 25-50% when an open divertor is closed on the common flux side of the outer divertor target ("semi-slot" divertor). Steady carbon buildup in the main plasma became significant during higher P_{IN} operation, and was largely due to sputtered carbon from graphite tiles on the horizontal surface above the pumping plenum entrance (and not from the "divertor floor"). Our results strongly suggest the necessity of further study before relying on either radiating divertor or poloidal flux expansion to adequately control divertor heat flux in high power, high performance DN plasmas.

*Work supported by the U.S. Department of Energy under DE-FC02-04ER54698, DEAC52007NA27344, DE-AC02-09CH11466, DE-FG02-04ER54761, and DE-AC04-94AL85000.

Paper Number

EX/P3-27

Country or International Organization

United States

Primary author: Dr PETRIE, Thomas W. (General Atomics)

Co-authors: MCLEAN, A.G. (Lawrence Livermore National Laboratory); LEONARD, A.W. (General Atomics); LASNIER, C.J. (Lawrence Livermore Laboratory); HOLCOMB, C.T. (Lawrence Livermore Laboratory); PACE,

D.C. (General Atomics); TURCO, F. (Columbia University); GUO, H.Y. (General Atomics); WATKINS, J.G. (Sandia National Laboratories); FERRON, J.R. (General Atomics); MAKOWSKI, M. (Lawrence Livermore National Laboratory); VAN ZEELAND, M.A. (General Atomics); FENSTERMACHER, M.E. (Lawrence Livermore Laboratory); GROEBNER, R.J. (General Atomics); ALLEN, S.L. (Lawrence Livermore Laboratory); OSBORNE, T. (General Atomics); LUCE, T.C. (General Atomics); SOLOMON, W.M. (Princeton Plasma Physics Laboratory)

Presenter: Dr PETRIE, Thomas W. (General Atomics)

Session Classification: Poster 3

Track Classification: EXS - Magnetic Confinement Experiments: Stability