

Summary Slide – FIP/2-2

Design and R&D Progress of Chinese HCCB TBM

Kaiming FENGa*, Xiaoyu WANGa, Yongjin FENGa, Yanjing CHENa, Zhou ZHAOa, Zaixin Lla, Pinghua WANGa, Qijie WANGa, Xingfu YEa, Fengchao ZHAOa, Long ZHANGa, Fen WANGa, Qixiang CAOa, Xinghua WUa, Yanling WANGa, Jun WANGa, Yang LIUa, Li YANGa, Yinfen CHENGa, Guo YUa, Jie LIUa, Xiaoyong WANGa, Mingchun ZHANGa, Baoping GONGa, Guoshu ZHANGa, Gang HUa, Hongbin LIAOa, Bin Zhoua, Chuanhong PANb, Xuru DUANa, and Chinese HCCB TBM Team

^a Southwestern Institute of Physics, Shuang Liu, Chengdu 610225, China
 ^b China International Nuclear Fusion Energy Program Execution Center, Beijing 100862, China


Southwestern Institute of Physics, Chengdu 610041, P.R. China Email: fengkm@swip.ac.cn; Fax:+86-28-82850956




Southwestern Institute of Physics

Main Design characteristics of CN HCCB TBM

- TBM structure: Sub-module arrangement
- Structure material: RAFM (CLF-1);
- Tritium breeder: Li₄SiO₄ pebble bed, 80%Li-6;
- Neutron multiplier: Be pebbles bed;
- Coolant and purge gas: Helium gas
- Coolant pressure: 8MPa
- Coolant temperature: 300 °C(inlet) -500 °C (outlet)
- Tritium production ratio (TPR): 0.0585g/d
- The updated design of Chinese solid breeder test blanket (CN HCCB TBM) is completed.





Cross-section of SB

backplate

Cap

First Wall

purge gas pipe

Coolant pipe

Updated design of CN HCCB TBM module



Southwestern Institute of Physics

Progress on R&D of CN HCCB TBM

- R&D on key components, structure and function materials, fabrication technology, etc., have being developed.
- Main R&D highlights:

-- Structure Material

A 500kg of RAFM(CLF-1)steel was recently produced by vacuum induction melting and electro-slag remelting method.

-- Neutron Multiplier

Exploration study of neutron multiplier Be pebbles fabrication technology using REP method has been done.

-- Tritium Breeder

Two kinds of the solid tritium breeder, Li₂TiO₃ and Li₄SiO₄, have been investigated in China.

-- Helium Test Loop

The design of a test helium loop working at high pressure (8MPa) and high temperature (550 C) prior to TBMs installation in ITER have been completed.

-- Test facility construction

An e-beam facility of 400kW have being constructed at SWIP.

-- Fabrication of FW and Sub-module


A 1/3 sized mock-up of FW and sub-module have being fabricated at SWIP.





Cooling plate


Sub-module segment







He Loop



Integrated design for AEU in Port Cell