



IAEA FEC 2016

Contribution ID: 547

Type: Poster

Particle simulation of plasma heat-flux dissipation by evaporated wall materials

Thursday, 20 October 2016 14:00 (4h 45m)

Erosions of the wall materials via melting, sputtering, and vaporization caused by the intense pulsed heat loads during ELMs and disruptions in the fusion devices are the serious concern. At the same time, experimental observations have shown that the intense heat flux causes the formation of vapor layer which dissipates further incoming plasma heat-flux. Understandings on these vapor-shielding phenomena largely influence the lifetime estimation of the wall armours. Thus, experimental and computational approaches are being taken. In the computational approach, the MHD fluid plasma models have been used to simulate this phenomena. These fluids approaches well describe behaviours of low-Z walls such as carbon. However, these fluid models do not include the sheath and non-Maxwellian effects. Thus, in order to study these plasma-vapor-wall interactions including these effects, a 1d3v particle-in-cell (PIC) code has been developed by the authors. Here, we firstly demonstrate the consistency of the simulation results comparing with experimental observation from a linear plasma device; PISCES-B. Decay lengths of the Be I line intensity from the wall were compared as a function of ejected Be amounts and agreements were obtained between them. Then, the calculations of rates of the plasma heat-flux dissipation by the evaporated vapor (Be, W) in a fusion reactor condition were taken. Compared with Be and W, it was found that W shows less effective dissipation even for the vapor pressure larger than its melting point. A cause of this smaller dissipation of W is the prompt re-deposition. The short ionization mean free path and re-deposition due to its large gyro radius leads the smaller contribution to the plasma heat-flux dissipation. These kinetic effects simulated by the particle code well explain the behaviour of the high-Z wall materials. Compared with these shielding performance of W, the efficient shielding of Be wall can largely reduce the erosion due to the transient heat load events.

Paper Number

TH/P6-27

Country or International Organization

Japan

Primary author: Dr IBANO, Kenzo (Osaka University)

Co-authors: Dr NISHIJIMA, Daisuke (Center for Energy Research, University of California in San Diego); Mr LEE, Heun Tae (Osaka University); YU, Jonathan (Center for Energy Research, University of California in San Diego); Dr BALDWIN, Matthew (Center for Energy Research, University of California in San Diego); Dr DOERNER, Russell (UCSD); Dr TAKIZUKA, Tomonori (Osaka University); Prof. UEDA, Yoshio (Osaka University)

Presenter: Dr IBANO, Kenzo (Osaka University)

Session Classification: Poster 6

Track Classification: THD - Magnetic Confinement Theory and Modelling: Plasma-material interactions; divertors, limiters, SOL