



IAEA FEC 2011

Contribution ID: 548

Type: Oral

Advances in the Steady-State Hybrid Regime in DIII-D – A Fully-Noninductive, ELM-Suppressed Scenario for ITER

Wednesday, 19 October 2016 16:40 (20 minutes)

A new regime with beta, collisionality and plasma shape relevant to the ITER steady-state mission has been attained in DIII-D using the fully noninductive hybrid scenario, including complete ELM suppression over a wide q_{95} window (between 5.9 and 7.1) and with little confinement degradation using resonant magnetic perturbation (RMP) coils. Furthermore, high-beta hybrid plasmas have been integrated with an Argon-based radiative divertor to advance divertor heat flux dissipation towards reactor relevance. Fully noninductive hybrids with simultaneous high beta ($\beta_N \leq 3.1$) and high confinement ($H_{98y2} \leq 1.4$) in the ITER similar shape have achieved zero surface loop voltage for up to two current relaxation times using efficient central current drive from ECCD and NBCD. This steady-state regime has been successfully integrated with ELM suppression by applying an odd parity $n=3$ RMP, which has only a minor impact on the pedestal pressure ($\sim 15\%$) and H_{98y2} ($\sim 10\%$). The odd parity RMP couples well to the high- q_{95} ITER steady-state case discussed here, whereas the even parity RMP couples better to the low- q_{95} ITER baseline scenario. The achieved $\beta_N (=3.1)$ equals the no-wall limit while remaining below the ideal with-wall limit ($=4.1$). Central ECCD is found to be effective in suppressing Alfvén eigenmodes (AE) and although the thermal transport increases during ECCD, this is mostly offset by the improved fast ion transport from AE suppression. Scaling these DIII-D hybrids to ITER's major radius and magnetic field while keeping the dimensionless parameters fixed except ρ^* yields a 9 MA plasma with 500 MW of fusion power and a required current drive power of 130 MW; this gives $Q_{fus} \approx 4$, close to the desired value of $Q_{fus} = 5$. In additional experiments that integrated the hybrid scenario with a radiating divertor, the combination of Argon seeding and strong Deuterium puffing more than doubles the plasma radiative power, up to 55% of the input power, with less than 10% increase in Z_{eff} and less than 5% reduction in H_{98y2} . IR camera measurements find that the peak heat flux in the upper, outer divertor falls by a factor of 2 (from 4.6 to 2.3 MW/m²) for the Argon-based radiative divertor.

This work was supported in part by the US Department of Energy under DE-FC02-04ER54698, DE-AC02-09CH11466, DE-FG02-04ER54761, DE-FG02-08ER54984, DE-AC52-07N27344 and DE-FG02-05ER54809.

Paper Number

EX/4-1

Country or International Organization

United States

Primary author: Dr PETTY, C. Craig (General Atomics)

Co-authors: GAROFALO, A.M. (General Atomics); HYATT, A.W. (General Atomics); GRIERSON, B.A. (Princeton Plasma Physics Laboratory); LASNIER, C. (Lawrence Livermore National Laboratory); PAZ-SOLDAN, C. (Gen-

eral Atomics); HOLCOMB, C.T. (Lawrence Livermore National Laboratory); ORLOV, D. (University of California-San Diego); PACE, D.C. (General Atomics); KOLEMEN, E. (Princeton Plasma Physics Laboratory); DOYLE, E.J. (University of California-Los Angeles); TURCO, F. (Columbia University); JACKSON, G.L. (General Atomics); FER- RON, J.R. (General Atomics); VAN ZEELAND, M.A. (General Atomics); LOGAN, N. (Princeton Plasma Physics Lab- oratory); TAYLOR, N.Z. (General Atomics); SNYDER, P.B. (General Atomics); NAZIKIAN, R. (Princeton Plasma Physics Laboratory); LA HAYE, R.J. (General Atomics); LUCE, T.C. (General Atomics); EVANS, T.E. (General Atomics); OSBORNE, T.H. (General Atomics); PETRIE, T.W. (General Atomics); SOLOMON, W.M. (Princeton Plasma Physics Laboratory); CHEN, X. (General Atomics)

Presenter: Dr PETTY, C. Craig (General Atomics)

Session Classification: Steady State and Hybrid scenarios

Track Classification: EXC - Magnetic Confinement Experiments: Confinement